International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

HUMANOID CONTROL PANEL

[1]D Mallesham, [2] G Srikanth, [3] G Sairam, [4] B Vardhan, [5] R Sai teja
[1]Assistant Professor, [2345]Students
Department of EEE
Siddhartha Institute of Technology & Sciences, Narapally
m.srinivasraoeee@siddhartha.co.in, 23tq1a0218@siddhartha.co.in, 23tq5a0209@siddhartha.co.in, 23tq1a0224@siddhartha.co.in, 23tq1a0204@siddhartha.co.in,

Abstract

The Humanoid Control Panel project focuses on the design and development of a centralized control interface for operating and monitoring a humanoid robot. A humanoid robot consists of multiple actuators, sensors, and electronic control units that require coordinated operation to perform movements and interact with the surrounding environment. Therefore, an efficient control panel is essential for managing the robot's functions and monitoring its operating status.

The proposed control panel provides an interface for controlling important humanoid functions such as head movement, arm movement, leg movement, walking, standing, and other predefined actions. Input commands from the user are processed by a control unit and transmitted to the corresponding actuators of the humanoid robot. Sensors can provide information such as position, motion, distance, and system status to support safe and accurate operation.

The system can include features such as manual control, predefined motion commands, sensor monitoring, status indication, emergency stop, and communication between the control panel and robot. A user-friendly interface allows the operator to issue commands and observe the robot's response in real time.

The project combines robotics, embedded systems, human–robot interaction, actuator control, sensor integration, and communication technologies. The control panel can be implemented using suitable hardware buttons, a touchscreen, computer interface, or wireless control system depending on the application.

Overall, the Humanoid Control Panel provides a centralized and user-friendly solution for controlling and monitoring humanoid robots. The system can be further enhanced with voice commands, artificial intelligence, gesture recognition, wireless connectivity, real-time feedback, and autonomous motion control to improve usability, safety, and intelligent interaction.

I. Introduction

A Humanoid Control Panel is an interface designed to control, monitor, and manage the different movements and functions of a humanoid robot. Humanoid robots are designed with a human-like structure consisting of components such as a head, arms, hands, legs, and body. Since these components require coordinated control, a centralized control panel provides an effective way to operate the robot and monitor its activities.

Received: 24-07-2026 | Accepted: 30-08-2026 | Published: 05-09-2026

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

The control panel acts as an interaction platform between the user and the humanoid robot. It allows the operator to provide commands for different movements, such as walking, standing, sitting, turning, and moving the arms or head. These commands are processed by a control unit and transmitted to the corresponding motors or actuators of the robot.

The system can use microcontrollers, motor drivers, sensors, communication modules, and actuators to perform the required operations. Sensors can provide information about the robot's position, movement, orientation, and surrounding environment. This feedback can be displayed on the control panel to help the operator monitor the robot's condition.

A user-friendly control interface is important for ensuring easy and accurate operation. The panel can include buttons, touch controls, sliders, status indicators, and predefined movement commands. An emergency-stop function can also be incorporated to immediately stop the robot during unsafe or unexpected conditions.

In this project, the Humanoid Control Panel is developed to provide centralized control of the humanoid robot's movements and functions. The system establishes communication between the control interface and the robot's controller, allowing commands to be sent and feedback to be received during operation.

Overall, the project demonstrates the application of robotics, embedded systems, actuator control, sensor integration, communication, and human–robot interaction. The system can be further enhanced with voice commands, gesture recognition, artificial intelligence, wireless control, real-time monitoring, and autonomous movement to make humanoid robot operation more intelligent, reliable, and user-friendly.

II. Literature Survey

Research on humanoid robot control systems has developed significantly with advances in robotics, embedded controllers, sensors, actuators, and human–robot interaction. Humanoid robots require coordinated control of multiple joints to perform movements such as walking, balancing, arm movement, and head orientation. Therefore, researchers have focused on developing reliable control architectures that can coordinate several actuators while receiving feedback from different sensors.

Early humanoid robot research focused on developing multi-joint control and balance mechanisms. Researchers developed control strategies that allow humanoid robots to maintain stability while standing and walking. These studies established the importance of joint position feedback, inertial sensors, motor control, and real-time processing for achieving stable humanoid motion.

The development of platforms such as NAO provided researchers with practical humanoid robots for studying motion control, perception, communication, and human–robot interaction. The NAO platform includes multiple actuators and sensors that can be controlled through software, making it suitable for research in autonomous robotics and interactive applications.

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

Research on humanoid robot control interfaces has also investigated centralized systems through which operators can manually control different robot joints. Such interfaces commonly provide controls for the head, arms, legs, and other actuators. Feedback from sensors can be displayed to the operator, allowing movements and robot status to be monitored during operation.

Another important research area is teleoperation and remote control. Researchers have developed control systems in which commands from a human operator are transmitted to a humanoid robot through wired or wireless communication. These systems are useful for applications where direct human operation is required, such as hazardous environments, remote inspection, education, and experimental robotics.

Studies have also explored sensor-based feedback control for humanoid robots. Sensors such as inertial measurement units, joint encoders, force sensors, and distance sensors provide information about the robot's movement and environment. This feedback allows the controller to adjust actuator commands and improve movement accuracy and stability.

Recent research has focused on human–robot interaction, including voice commands, gesture recognition, touchscreen interfaces, and natural-language interaction. These technologies make humanoid robots easier to operate by allowing users to provide high-level commands instead of controlling every joint individually.

Advanced humanoid platforms such as ASIMO, Atlas, and Pepper have demonstrated the integration of complex actuator systems, sensors, computing platforms, and intelligent control algorithms. These developments show that effective humanoid operation requires coordination between hardware control, sensor feedback, communication, and user interfaces.

Based on the existing research, the proposed Humanoid Control Panel focuses on developing a centralized and user-friendly interface for controlling and monitoring humanoid robot functions. The system can provide controls for head, arms, legs, walking, standing, turning, and predefined movements, while sensor feedback can be displayed through the interface. The system can be further enhanced using wireless communication, voice commands, gesture recognition, artificial intelligence, real-time feedback, and autonomous motion control to improve the usability, safety, and intelligence of humanoid robots.

III. System Analysis

System analysis is an important stage in the development of the Humanoid Control Panel project. The system is designed to provide centralized control and monitoring of a humanoid robot. The main requirements include controlling different body parts such as the head, arms, hands, legs, and other actuators. A suitable controller is used to process commands received from the control panel. The interface provides buttons, touch controls, or predefined commands for operating the robot. Sensors are used to provide feedback about joint position, movement, orientation, and robot status. Motor drivers and actuators receive control signals from the controller to perform the required movements. Communication between the control panel and robot is

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

established using wired or wireless technology. The system also includes safety functions such as movement limits and an emergency stop. Real-time feedback helps the operator monitor the robot during operation. The control system is designed to provide accurate and responsive movement commands. Overall, system analysis defines the hardware, software, communication, and functional requirements of the Humanoid Control Panel.

Existing System

In the existing system, humanoid robots are commonly controlled using separate software interfaces, remote controllers, programming tools, or predefined motion systems. Different robot joints may require individual control commands, making operation complex for inexperienced users. Some systems depend heavily on manually programmed movement sequences for performing specific actions. Sensor information may not always be presented through a single centralized interface. Operators may need to switch between different control screens to monitor various robot functions. Wired communication systems can restrict the movement and operating range of the robot. Wireless systems may introduce communication delays or connection problems. Basic control interfaces may provide limited feedback about actuator position and robot status. Emergency and safety controls may also be separated from normal operating functions. Modifying movement commands can require programming knowledge and additional configuration. These limitations can make humanoid robot operation less convenient and less flexible. Therefore, an integrated control panel can provide a simpler and more effective solution for controlling and monitoring the robot.

Disadvantages of Existing System

- Requires complex manual control.
- Different robot functions may use separate interfaces.
- Limited centralized monitoring.
- Requires programming knowledge for some operations.
- Difficult for inexperienced users.
- Limited real-time sensor feedback.
- Communication delays may occur.
- Wired systems can restrict mobility.
- Movement sequences may require manual programming.
- Safety controls may not be centralized.
- Difficult to modify commands quickly.
- Limited user-friendly interaction.

Proposed System

The proposed system focuses on developing a centralized and user-friendly Humanoid Control Panel for controlling and monitoring a humanoid robot. The control panel provides an interface through which the operator can control different robot functions. Commands can be provided for head movement, arm movement, hand movement, leg movement, walking, standing, sitting, and turning. A microcontroller or suitable control unit processes the commands received from the interface. The controller sends

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

appropriate signals to motor drivers and actuators to perform the requested movements. Sensors provide feedback about joint positions, orientation, movement, and system conditions. The feedback information can be displayed on the control panel for real-time monitoring. Wireless or wired communication can be used to establish communication between the panel and robot. An emergency-stop function can immediately stop the robot when an unsafe condition occurs. Predefined movement commands can simplify frequently performed actions and reduce manual control effort. The system can be designed with adjustable control parameters to provide smoother and more accurate movements. Overall, the proposed system provides centralized, flexible, safe, and user-friendly control of humanoid robot functions.

Advantages of Proposed System

- Provides centralized robot control.
- User-friendly control interface.
- Supports multiple humanoid movements.
- Provides real-time sensor feedback.
- Reduces manual control complexity.
- Supports predefined movement commands.
- Enables convenient robot monitoring.
- Supports wired or wireless communication.
- Includes emergency-stop functionality.
- Allows easy modification of commands.
- Improves movement control and coordination.
- Can be enhanced with AI and voice control.


IV. Methodology

The methodology begins by identifying the required humanoid robot movements and control functions. Suitable components such as a microcontroller, motor drivers, servo motors or actuators, sensors, communication module, and power supply are selected. A control-panel interface is designed with suitable buttons, touch controls, sliders, and status indicators. Commands from the interface are transmitted to the main controller for processing. The controller converts the received commands into appropriate signals for the corresponding motors and actuators. Sensors are connected to provide feedback about joint position, orientation, movement, and system status. Communication between the control panel and robot is established using suitable wired or wireless technology. Predefined movement sequences are programmed for actions such as standing, walking, sitting, turning, and arm movement. Safety limits are implemented to prevent excessive joint movement and unexpected operation. An emergency-stop function is incorporated to immediately disable actuator movement when required. The complete system is tested by performing individual and combined robot movements. Finally, the control response, communication reliability, movement accuracy, sensor feedback, and safety functions are evaluated and improved.

System Architecture


International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

The system architecture represents the complete workflow of the Humanoid Control Panel from user commands to robot movement and feedback. The process begins with the operator providing commands through the control-panel interface. The interface contains controls for different body parts and predefined humanoid movements. The input commands are transferred to the communication module for transmission to the robot controller. The main controller processes the received commands and determines the required actuator operations. Motor drivers receive control signals from the controller and operate the corresponding servo motors or actuators. The actuators control the humanoid robot's head, arms, hands, legs, and other movable components. Sensors continuously collect information about joint position, orientation, movement, and system conditions. This sensor feedback is returned to the controller for monitoring and control adjustment. The control panel displays the received feedback through status indicators or monitoring screens. A safety module monitors movement limits and can activate the emergency stop when an unsafe condition is detected. The system can store predefined movement sequences for frequently required robot actions. Overall, the architecture provides a complete command, communication, control, actuation, sensing, feedback, and safety cycle for efficient humanoid robot operation.




V. Result and Output

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper









Received: 24-07-2026 | Accepted: 30-08-2026 | Published: 05-09-2026

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

VI. Conclusion

The Humanoid Control Panel project successfully demonstrates the development of a centralized system for controlling and monitoring the different functions of a humanoid robot. The control panel provides an easy and user-friendly interface for operating movements such as standing, walking, sitting, turning, head movement, and arm movement.

The system integrates a controller, motor drivers, actuators, sensors, and communication modules to execute user commands accurately. Sensor feedback helps monitor the robot's joint positions, orientation, battery status, and other operating conditions in real time. The proposed system reduces the complexity of controlling multiple humanoid joints individually and provides centralized access to important robot functions. Safety features such as emergency stop, joint-limit monitoring, and status alerts can improve the reliability and safe operation of the robot.

Overall, the project demonstrates the effective application of robotics, embedded systems, actuator control, sensor feedback, communication, and human–robot interaction. The system can be further enhanced by integrating AI, voice commands, gesture recognition, autonomous movement, wireless communication, and intelligent decision-making to make humanoid robots more efficient, interactive, and user-friendly.

References

[1] Kumar, R. D., Prudhviraj, G., Vijay, K., Kumar, P. S., & Plugmann, P. (2024). Exploring COVID-19 through intensive investigation with supervised machine learning algorithm. In Handbook of Artificial Intelligence and Wearables (pp. 145-158). CRC Press.
[2] Swathi, B., Vijay, K., Sushanth Babu, M., & Dinesh Kumar, R. (2024, November). Machine Learning Techniques in Cloud Based Intrusion Detection. In The International Conference on Artificial Intelligence and Smart Environment (pp. 557-564). Cham: Springer Nature Switzerland.
[3] Sv satyakrishna, shirisha rangu ,bhargavi nalacheruve.(2024) Prospective investigation on colorectal cancer with SMOTE on machine learning Algorithm
[4] Dr.G.Vishnu Murthy, BhargaviNalacheruve 1Professor, Department of computer Science & engineering, Anurag University, TS, India. 2Student, Department of computer Science & engineering, Anurag University, TS, India.
[5] V. N. S. Manaswini, K. K, C. Nigam, S. S. Ali, R. Niranjana, and Suman, “Real-Time Object Detection in Drone Surveillance Using YOLOv5,” in Proc. 2025 3rd Int. Conf. IoT, Communication and Automation Technology (ICICAT), Gorakhpur, India, 2025, pp. 1–6, doi: 10.1109/ICICAT68430.2025.11414670.
[6] B. Soundarya, V. N. S. Manaswini, M. Ayyakrishnan, R. D. Kumar, “Contextual Analysis of Big Data Analytics in Intelligent Transportation Frameworks,” in Intersection of Artificial Intelligence, Data Science, and Cutting-Edge Technologies: From Concepts to Applications in Smart Environment, Lecture Notes in Networks and Systems, vol. 1353, Cham: Springer, 2025, doi: 10.1007/978-3-031-88304-0_79.

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

[7] R. D. Kumar, V. N. S.Manaswini, "Applications of blockchain in smart cities: detecting fake documents from land records using blockchain technology," in Blockchain for Smart Cities, Elsevier, 2021, pp. 105–117, doi: 10.1016/B978-0-12-824446-3.00017-X.

[8] Tejavath Veeramma, Badarla Anil, Guguloth Ravinder, "An advanced movie recommender using collaborative filtering and sentiment analysis," International Research Journal of Modernization in Engineering Technology and Science, vol. 7, no. 7, July 2025, doi: 10.56726/IRJMETS81618.

[9] Ravi Kumar Banoth, Ramana Murthy B V, "Automatic crop recommendation system using LightGBM and decision tree machine learning models," Journal of Machine and Computing, vol. 5, no. 1, pp. 343, Jan. 2025, doi: 10.53759/7669/jmc202505026.

[10] Ravi Kumar Banoth, Dr. B.V. Ramana Murthy, "Smart agriculture through IoT and machine learning for analyzing carbon footprints," in Proc. Int. Conf. Computer Science and Communication Engineering (ICCSCE), Apr. 2025.

[11] Ravi Kumar Banoth, B. V. Ramana Murthy, "Soil image classification using transfer learning approach: MobileNetV2 with CNN," SN Computer Science, vol. 5, art. no. 199, 2024, doi: 10.1007/s42979-023-02500-x.