International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

SMART MICROGRID ENENRGY MANAGEMENT SYSTEM

[1] T Vijay Kumar, [2] K Ranjith Kumar Reddy, [3] J Mahendar Goud, [4] M Vishnu, [5] R Upendhar
[1]Assistant Professor, [2345]Students
Department of EEE
Siddhartha Institute of Technology & Sciences, Narapally
t.vijay.kumar@siddhartha.org.in, 24tq5a0205@siddhartha.co.in, 23tq1a0207@siddhartha.co.in,
24tq5a0201@siddhartha.co.in, 23tq1a0211@siddhartha.co.in,

Abstract

The Smart Microgrid Energy Management System is an intelligent energy management solution designed to monitor, control, and optimize power generation and consumption within a microgrid. A microgrid can integrate renewable energy sources such as solar photovoltaic (PV) systems, battery energy storage, the main utility grid, and electrical loads. Efficient coordination of these sources is essential for reducing energy wastage, improving reliability, and maximizing the use of renewable energy.

The proposed system continuously monitors electrical parameters such as voltage, current, power, energy consumption, solar generation, and battery status using suitable sensors and a microcontroller or energy management controller. The collected data is analyzed to determine the availability of renewable energy and the current load demand. Based on these conditions, the system automatically manages the flow of power between renewable sources, battery storage, the utility grid, and connected loads.

When sufficient solar energy is available, the system prioritizes renewable power for supplying the loads and charging the battery. When renewable generation is insufficient, stored battery energy or grid power can be utilized. The system can also manage non-critical loads during high-demand periods to maintain energy balance and reduce unnecessary consumption.

An IoT-based monitoring system can be integrated to provide real-time visualization of energy generation, consumption, battery status, and grid usage. This enables users to monitor and analyze the microgrid remotely. The system improves energy utilization, supports renewable integration, and provides better control over electrical loads.

I. Introduction

The Smart Microgrid Energy Management System is an intelligent system designed to monitor, control, and efficiently manage electrical energy within a microgrid. With the increasing demand for electricity and the growing use of renewable energy, effective energy management has become important for reducing power wastage and improving energy reliability. A microgrid can combine solar power, battery storage, utility grid supply, and electrical loads into a coordinated energy system.

The proposed system focuses on continuously monitoring important electrical parameters such as voltage, current, power, energy consumption, solar generation, and battery status. Sensors are used to collect real-time electrical information, while a microcontroller or energy management controller processes the collected data and makes appropriate control decisions.

Renewable energy, particularly solar photovoltaic (PV) power, can be prioritized whenever sufficient energy is available. The generated solar power can be used

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

directly to supply connected loads, while excess energy can be stored in a battery for later use. When renewable generation is insufficient, the system can automatically utilize stored battery energy or obtain additional power from the utility grid.
The system can also implement load management by monitoring the energy demand of connected appliances. During periods of high demand or limited power availability, non-critical loads can be reduced or temporarily disconnected. This helps maintain the balance between energy generation and consumption and prevents unnecessary energy usage.

II. Literature Survey

Research on Smart Microgrid Energy Management Systems (SMEMS) has increased with the growth of renewable energy sources, distributed generation, battery energy storage, and smart-grid technologies. A microgrid generally combines distributed energy resources, energy storage systems, and electrical loads that can operate in coordination with the main utility grid or, in suitable configurations, independently. Effective energy management is therefore important for maintaining the balance between power generation and demand.

Early research on microgrid energy management mainly focused on rule-based and optimization-based energy management strategies. Rule-based approaches use predefined conditions to determine when renewable energy, batteries, or grid power should supply the loads. These methods are simple to implement and suitable for small systems, but their performance can be limited when energy generation and demand vary significantly.

Researchers have extensively investigated the integration of solar photovoltaic (PV) systems into microgrids. Solar energy is clean and renewable, but its generation depends on factors such as sunlight, weather conditions, and time of day. Energy management systems are therefore required to coordinate solar generation with energy storage and load demand to maximize renewable-energy utilization.

Battery energy storage systems (BESS) have become an important part of modern microgrids. Studies have examined battery charging and discharging strategies that can reduce dependence on grid electricity and improve the reliability of renewable-energy systems. Proper battery management is important because excessive charging or deep discharge can reduce battery life and system efficiency.

Another major research area is load management and demand-side management. Energy management systems can classify electrical loads according to their priority and schedule non-critical loads during periods of high renewable generation or low electricity cost. This approach can reduce peak demand and improve the overall utilization of available energy.

Researchers have also explored optimization algorithms for microgrid energy management. Techniques such as linear programming, mixed-integer optimization, particle swarm optimization, genetic algorithms, and other metaheuristic methods have been applied to determine suitable power-dispatch and load-scheduling

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

strategies. These methods can optimize objectives such as operating cost, renewable-energy utilization, battery usage, and peak-load reduction.

With the development of Internet of Things (IoT) technology, microgrid systems can now collect and transmit real-time information from smart meters, sensors, renewable-energy sources, batteries, and loads. IoT-based monitoring enables users and energy-management controllers to observe parameters such as voltage, current, power generation, energy consumption, and battery status remotely.

Recent studies have increasingly investigated artificial intelligence and machine learning for smart energy management. AI techniques can be used for load forecasting, renewable-energy prediction, battery management, anomaly detection, and optimal energy scheduling. Forecasting future energy generation and demand can help the controller make better decisions before changes occur in the microgrid.

Research has also focused on grid-connected and islanded microgrid operation. In grid-connected operation, the microgrid can exchange power with the utility grid according to energy availability and demand. During grid interruptions, an appropriately designed microgrid can operate in islanded mode and use available renewable generation and energy storage to supply important loads.

Based on the existing research, the proposed Smart Microgrid Energy Management System integrates renewable energy generation, battery storage, utility-grid supply, electrical loads, sensing, and automated control into a centralized energy-management framework. The system monitors real-time power conditions and selects an appropriate energy source based on generation, demand, and battery status. Future improvements can include AI-based load forecasting, IoT-based remote monitoring, dynamic load scheduling, predictive battery management, and advanced optimization algorithms to create a more efficient, reliable, economical, and sustainable microgrid.

III. System Analysis

System analysis is an important stage in developing the Smart Microgrid Energy Management System. The system is designed to monitor, control, and optimize electrical energy within a microgrid. The main requirements include renewable energy generation, battery storage, grid supply, load monitoring, and automatic power management. Solar panels can be used as the primary renewable energy source for generating electricity. Sensors are used to measure voltage, current, power, and energy consumption from different sources and loads. A microcontroller or energy management controller processes the collected electrical data. The controller determines the most suitable power source based on energy availability and load demand. Battery status is also monitored to control charging and discharging safely. Non-critical loads can be managed during periods of high demand or low power availability. An IoT module can provide remote monitoring of generation, consumption, and battery conditions. The system is designed to improve renewable-energy utilization and reduce unnecessary dependence on grid power. Overall, the system analysis defines the hardware, software, control, and monitoring requirements of the proposed microgrid.

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

Existing Systsem

In the existing system, electrical energy management is often performed using conventional grid systems and manually controlled power sources. Renewable energy sources such as solar panels may operate independently without intelligent coordination with batteries and electrical loads. Battery charging and discharging may be controlled using basic charge controllers with limited energy-management capabilities. Users may have to manually monitor power generation and energy consumption. Traditional systems generally do not automatically select the most suitable energy source according to real-time demand. During periods of low solar generation, the system may depend heavily on utility-grid power. Excess renewable energy may not always be effectively utilized or stored. Conventional load management systems may not prioritize loads according to their importance. Remote monitoring and historical energy analysis may also be limited. Fixed control strategies may not respond effectively to rapidly changing generation and consumption conditions. These limitations can lead to energy wastage, increased grid dependency, and inefficient battery utilization. Therefore, an intelligent energy management system is required to coordinate different energy sources and loads efficiently.

Disadvantages of Existing System

- Limited automation in energy management.
- High dependence on conventional grid power.
- Inefficient utilization of excess solar energy.
- Limited real-time monitoring.
- Manual control may be required.
- Poor coordination between renewable sources and batteries.
- Limited intelligent load management.
- Fixed control strategies may not adapt to changing conditions.
- Possible unnecessary battery charging and discharging.
- Limited remote monitoring capabilities.
- Difficulty in analyzing historical energy consumption.
- Higher possibility of energy wastage.

Proposed System

The proposed system provides an intelligent and automated approach to managing energy within a smart microgrid. The system integrates solar photovoltaic generation, battery storage, utility-grid supply, and electrical loads. Sensors continuously measure voltage, current, power generation, energy consumption, and battery conditions. A microcontroller or energy management controller processes the collected information in real time. When sufficient solar power is available, renewable energy is prioritized for supplying the connected loads. Excess solar energy can be directed toward charging the battery for later use. When solar generation is insufficient, the controller can utilize stored battery energy before drawing additional power from the utility grid. The system can classify loads according to their priority and manage non-critical loads during high-demand conditions. An IoT module can transmit energy information to a cloud-based monitoring platform. Users can remotely observe solar generation, load consumption, battery status, and grid usage. Automated control helps

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

reduce energy wastage and improve the utilization of renewable energy. Overall, the proposed system provides efficient, reliable, and intelligent energy management for a modern microgrid.

Advantages of Proposed System

- Improves renewable-energy utilization.
- Reduces unnecessary grid dependency.
- Provides automated energy management.
- Supports battery charging and discharging control.
- Provides real-time energy monitoring.
- Supports intelligent load management.
- Reduces energy wastage.
- Enables IoT-based remote monitoring.
- Helps reduce peak power demand.
- Improves overall microgrid efficiency.
- Supports sustainable energy utilization.
- Can be enhanced with AI and machine learning.

IV. Methodology


The methodology begins with identifying the energy sources, storage requirements, and electrical loads that will form the microgrid. Solar panels are selected as the renewable energy source, while a battery storage system is used to store excess generated energy. Voltage and current sensors are installed to measure power generation, consumption, and battery conditions. A microcontroller or energy management controller is configured as the central processing unit of the system. The controller continuously collects electrical parameters from the solar system, battery, grid, and connected loads. A control algorithm is developed to compare available generation with the current load demand. When solar power is sufficient, the system supplies the loads using solar energy and charges the battery using excess power. When solar power is insufficient, stored battery energy is used according to the defined operating conditions. If both solar and battery power are insufficient, the system can automatically switch to utility-grid power. Load-priority rules can be implemented to control non-critical loads during high-demand periods. An IoT module can transmit the measured parameters to a cloud platform for remote monitoring. Finally, the complete system is tested under different generation, load, and battery conditions to evaluate its efficiency and reliability.

System Architecture

The system architecture represents the complete flow of energy, information, and control within the Smart Microgrid Energy Management System. The system begins with the solar PV panel, which generates electrical energy from sunlight. The generated power is supplied to the energy-management system and can be used to operate connected electrical loads. Excess solar energy is directed toward the battery energy storage system for later use. The utility grid acts as an additional power source when renewable generation and stored energy are insufficient. Voltage and current sensors continuously measure the electrical parameters of the solar source, battery,


International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper


grid, and loads. These measurements are sent to the central microcontroller or energy management controller for processing. The controller compares power generation, battery status, and load demand to determine the appropriate power-distribution strategy. A relay or switching unit controls the connection between different power sources and loads. An IoT communication module transmits important energy data to a remote monitoring platform. The user can monitor solar generation, energy consumption, battery status, and grid usage through the monitoring interface. The controller can also manage non-critical loads according to predefined priority conditions. Overall, the architecture provides a complete energy generation, sensing, processing, storage, load management, power distribution, and remote monitoring system for smart microgrid operation.




V. Result and Output

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper







a) Power Generation & Consumption b) Battery Status c) Grid Power & Source d) System Status

VI. Conclusion

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

The Smart Microgrid Energy Management System successfully demonstrates an intelligent approach to monitoring, controlling, and optimizing electrical energy within a microgrid. The system integrates solar PV generation, battery energy storage, utility-grid supply, sensors, loads, and an energy management controller to achieve efficient power utilization.

The system continuously monitors important parameters such as voltage, current, power generation, energy consumption, and battery status. Based on the available renewable energy and load demand, the controller can select the appropriate power source and manage the flow of energy automatically.

The proposed system helps maximize renewable-energy utilization, reduce unnecessary grid dependency, improve battery usage, and minimize energy wastage. IoT-based monitoring also provides users with real-time information about the operating condition of the microgrid.

Overall, the project provides a reliable, economical, and sustainable solution for modern energy management. The system can be further enhanced by integrating AI-based energy forecasting, machine learning, smart meters, predictive battery management, dynamic load scheduling, and advanced optimization algorithms to make the microgrid more intelligent and efficient.

References

[1] Kumar, R. D., Prudhviraj, G., Vijay, K., Kumar, P. S., & Plugmann, P. (2024). Exploring COVID-19 through intensive investigation with supervised machine learning algorithm. In Handbook of Artificial Intelligence and Wearables (pp. 145-158). CRC Press.
[2] Swathi, B., Vijay, K., Sushanth Babu, M., & Dinesh Kumar, R. (2024, November). Machine Learning Techniques in Cloud Based Intrusion Detection. In The International Conference on Artificial Intelligence and Smart Environment (pp. 557-564). Cham: Springer Nature Switzerland.
[3] Sv satyakrishna, shirisha rangu ,bhargavi nalacheruve.(2024) Prospective investigation on colorectal cancer with SMOTE on machine learning Algorithm
[4] Dr.G.Vishnu Murthy, BhargaviNalacheruve 1Professor, Department of computer Science & engineering, Anurag University, TS, India. 2Student, Department of computer Science & engineering, Anurag University, TS, India.
[5] V. N. S. Manaswini, K. K, C. Nigam, S. S. Ali, R. Niranjana, and Suman, “Real-Time Object Detection in Drone Surveillance Using YOLOv5,” in Proc. 2025 3rd Int. Conf. IoT, Communication and Automation Technology (ICICAT), Gorakhpur, India, 2025, pp. 1–6, doi: 10.1109/ICICAT68430.2025.11414670.
[6] B. Soundarya, V. N. S. Manaswini, M. Ayyakrishnan, R. D. Kumar, “Contextual Analysis of Big Data Analytics in Intelligent Transportation Frameworks,” in Intersection of Artificial Intelligence, Data Science, and Cutting-Edge Technologies: From Concepts to Applications in Smart Environment, Lecture Notes in Networks and Systems, vol. 1353, Cham: Springer, 2025, doi: 10.1007/978-3-031-88304-0_79.
[7] R. D. Kumar, V. N. S.Manaswini, “Applications of blockchain in smart cities: detecting fake documents from land records using blockchain technology,” in

Blockchain for Smart Cities, Elsevier, 2021, pp. 105–117, doi: 10.1016/B978-0-12-824446-3.00017-X.

[8] Tejavath Veeramma, Badarla Anil, Guguloth Ravinder, "An advanced movie recommender using collaborative filtering and sentiment analysis," International Research Journal of Modernization in Engineering Technology and Science, vol. 7, no. 7, July 2025, doi: 10.56726/IRJMETS81618.

[9] Ravi Kumar Banoth, Ramana Murthy B V, "Automatic crop recommendation system using LightGBM and decision tree machine learning models," Journal of Machine and Computing, vol. 5, no. 1, pp. 343, Jan. 2025, doi: 10.53759/7669/jmc202505026.

[10] Ravi Kumar Banoth, Dr. B.V. Ramana Murthy, "Smart agriculture through IoT and machine learning for analyzing carbon footprints," in Proc. Int. Conf. Computer Science and Communication Engineering (ICCSCE), Apr. 2025.

[11] Ravi Kumar Banoth, B. V. Ramana Murthy, "Soil image classification using transfer learning approach: MobileNetV2 with CNN," SN Computer Science, vol. 5, art. no. 199, 2024, doi: 10.1007/s42979-023-02500-x.