International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

HUMAN FOLLOWING ROBOT

[1]P Rushikesh Rao, [2] P Sreeja, [3] V Shylini, [4] K Madhusudan rao, [5] CH Rajesh
[1]Assistant Professor, [2345]Students
Department of EEE
Siddhartha Institute of Technology & Sciences, Narapally
patlollarushikeshrao.eee@siddhartha.co.in, 24tq5a0204@siddhartha.co.in,
24tq5a0206@siddhartha.co.in, 23tq1a0201@siddhartha.co.in, 23tq1a0212@siddhartha.co.in,

Abstract

The Human Following Robot project focuses on the design and development of an autonomous mobile robot capable of detecting, tracking, and following a person without continuous manual control. Such robots can be useful in applications such as personal assistance, luggage transportation, healthcare support, warehouses, and service robotics. The main objective of the project is to develop a robot that can maintain a suitable distance from a person while moving safely and efficiently.

The proposed robot consists of components such as a microcontroller, motors, motor driver, sensors, camera, and power supply. Distance and motion sensors are used to detect the position of a person and obstacles in the robot's path. A camera or suitable human-detection sensor can be integrated to identify and track the target person. The microcontroller processes the sensor information and generates appropriate control signals for the motors.

Based on the detected person's position and distance, the robot can move forward, backward, left, or right to maintain the required following distance. Obstacle detection helps the robot avoid collisions while following the person. The control algorithm continuously receives sensor information and adjusts the robot's movement according to changes in the person's position.

The system combines robotics, embedded systems, sensors, motor control, and human-tracking technology to achieve autonomous following behavior. The design can be further improved using artificial intelligence and computer vision techniques for more accurate person identification and tracking.

I. Introduction

A Human Following Robot is an autonomous mobile robotic system designed to detect and follow a person without requiring continuous manual control. The robot can be useful in various applications such as personal assistance, luggage transportation, healthcare, warehouses, hospitals, and service industries. The main purpose of the system is to make transportation and assistance tasks easier by allowing the robot to automatically follow a designated person.

The robot uses a combination of sensors, a microcontroller, motors, motor driver, camera, and power supply to perform its functions. Sensors are used to detect the presence and distance of a person and identify obstacles in the robot's path. A camera or human-detection sensor can be used to recognize and track the target person.

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

The microcontroller acts as the main processing unit of the robot. It receives information from the sensors and determines the appropriate movement of the robot. Depending on the person's position, the robot can move forward, backward, left, or right while attempting to maintain a suitable distance from the person.

Obstacle detection is an important feature of the system because the robot must safely navigate its surroundings while following the target. When an obstacle is detected, the controller can change the robot's direction or stop the motors to avoid a collision.

II. Literature Survey

Research on Human Following Robots has developed significantly with advances in mobile robotics, computer vision, sensors, navigation, and human–robot interaction. Person-following is considered an important capability for service and companion robots used in areas such as healthcare, personal assistance, logistics, manufacturing, and social interaction. Researchers have studied different approaches for detecting a person, tracking the target, planning the robot's movement, and maintaining a safe following distance.

Earlier research investigated the use of vision-based human recognition for person-following robots. Alvarez-Santos and colleagues studied color and texture features obtained from a camera mounted on a mobile robot to recognize and discriminate the person being followed. Their work demonstrated the importance of reliable human identification for achieving stable following behavior.

Researchers have also explored laser-based human detection. A human-following mobile robot using a laser range scanner was developed to detect a person's legs and estimate the target's position. The same sensing approach could also provide information about surrounding obstacles, allowing the robot to combine human following with collision avoidance.

Another important research area is the development of tracking and control algorithms. Studies have shown that a person-following robot generally requires three major capabilities: target tracking, following control, and suitable hardware. Sensor fusion involving vision and range sensors can improve target tracking, while control algorithms convert the detected person's position into appropriate robot movement.

More advanced research has investigated real-time human tracking in environments containing multiple people. A 2021 study proposed a stereo-camera-based tracking method using human detection, color information, block matching, and Kalman-filter prediction to identify and follow a selected person. The approach demonstrates how computer vision and prediction can help maintain tracking when the environment becomes more challenging.

Researchers have also emphasized the importance of socially aware behavior. A review of person-following robots examined applications, robot platforms, environments, following strategies, human–robot communication, and evaluation methods. The research identified social interaction and understanding user needs as important areas that require further development.

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

Recent comprehensive research has expanded the field toward perception, tracking, path planning, obstacle avoidance, and human–robot interaction. A 2025 review examined these technologies across applications including healthcare, personal assistance, logistics, and tour guidance, while also identifying continuing challenges in reliable perception, navigation, and interaction.

Recent work has also highlighted multi-sensor fusion for person-following systems. Combining information from different sensors can improve target recognition, path planning, and obstacle avoidance, particularly when the person temporarily becomes difficult to detect or when the robot operates in a complex environment.

Based on the existing literature, the proposed Human Following Robot focuses on developing a mobile robotic system capable of detecting a target person, maintaining a suitable distance, following the person's movement, and avoiding obstacles. The system can combine a microcontroller, ultrasonic or distance sensors, camera, motor driver, and DC motors to achieve autonomous movement. Further improvements can include AI-based person recognition, computer vision, sensor fusion, LiDAR, GPS, and advanced obstacle avoidance to improve tracking accuracy, safety, and reliability.

III. System Analysis

System analysis is an important stage in the development of the Human Following Robot project. The system is designed to detect a person and follow the target automatically without continuous manual control. Important requirements such as person detection, distance measurement, movement control, obstacle detection, and power management are considered. A microcontroller is used as the main control unit for processing sensor information and controlling the robot. Suitable sensors are used to detect the target person's position and distance from the robot. A camera can also be integrated for accurate human detection and tracking. Motors and a motor driver are used to control the movement of the robot in different directions. The control algorithm determines whether the robot should move forward, stop, or turn based on the detected target position. Obstacle detection is included to prevent collisions during movement. The robot continuously receives sensor information and adjusts its movement according to the person's changing position. The system is designed to maintain a suitable distance between the robot and the target person. Overall, system analysis helps define the hardware, software, and functional requirements required for reliable human-following operation.

Existing System

In the existing system, human-following and assistance tasks are often performed manually or using basic remote-controlled robotic systems. Conventional robots generally require a user to operate the robot using a remote control or mobile application. Some basic following robots use distance sensors to detect objects and move toward them without identifying whether the object is actually a person. These systems may have difficulty distinguishing the target person from other objects or people in the environment. Simple sensor-based systems can also lose the target when the person changes direction or moves outside the sensor's detection range. Fixed-distance sensors provide limited information about the person's position and

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

movement. Obstacle detection may also be limited in basic robotic systems. Manual intervention may therefore be required when the robot encounters obstacles or loses the target. Camera-based systems can provide better information but may require more processing capability. Traditional systems may also have limited adaptability to crowded or dynamic environments. These limitations create a need for a more intelligent and reliable human-following mechanism. Therefore, integrating multiple sensors, automatic control, and vision-based detection can improve the performance of the robot.

Disadvantages of Existing System

- Requires manual control in many systems.
- Basic sensors cannot reliably identify a person.
- Difficult to distinguish the target from other objects.
- Limited detection range.
- May lose the target during movement.
- Limited performance in crowded environments.
- Basic systems have poor obstacle avoidance.
- Requires frequent human intervention.
- Fixed sensors provide limited environmental information.
- Camera-based systems may require high processing power.
- Difficult to maintain a constant following distance.
- Limited adaptability to changing environments.

Proposed System

The proposed system focuses on developing an autonomous Human Following Robot capable of detecting and following a designated person automatically. The robot uses a microcontroller as the central processing unit for coordinating sensors, motors, and other components. A camera or suitable distance and motion sensors can be used to detect the target person and determine their relative position. The robot continuously processes sensor information to decide the appropriate movement direction. Depending on the person's position, the robot can move forward, turn left, turn right, or stop. A suitable following distance is maintained between the robot and the target person. Obstacle detection sensors are used to identify objects in the robot's path and prevent collisions. The motor driver receives control signals from the microcontroller and operates the motors accordingly. The robot can follow the target through a predefined or dynamically changing path. The system reduces the need for continuous manual operation and improves mobility and convenience. Camera-based tracking can be added to improve target identification and tracking accuracy. Overall, the proposed system provides an automated, flexible, and practical solution for human-following applications.

Advantages of Proposed System

- Provides autonomous human following.
- Reduces manual control requirements.
- Maintains a suitable following distance.
- Supports automatic directional movement.

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

- Provides obstacle detection.
- Reduces collision risk.
- Can use camera-based person detection.
- Improves target tracking capability.
- Supports real-time sensor processing.
- Useful for luggage and personal assistance.
- Can be enhanced using AI and computer vision.
- Provides a flexible and practical robotic solution.


IV. Methodology

The methodology begins by identifying the requirements of the Human Following Robot, including target detection, following distance, movement, obstacle avoidance, and power requirements. Suitable hardware components such as a microcontroller, sensors, camera, motor driver, DC motors, wheels, and battery are selected. The robot chassis is designed to support all the required mechanical and electronic components. Sensors are positioned appropriately to detect the target person and obstacles in the surrounding environment. The camera or human-detection sensors provide information about the target person's position and distance. The microcontroller processes the sensor information and determines the required movement of the robot. Motor control logic is implemented to move the robot forward, turn left, turn right, or stop according to the target's position. Obstacle avoidance logic is incorporated to prevent the robot from colliding with objects. The control program continuously updates the robot's movement based on changing sensor values. The complete system is tested under different distances, directions, and obstacle conditions. Tracking performance and following accuracy are evaluated during testing. Finally, the system can be improved by adjusting the control algorithm, sensor positions, and following parameters to achieve smoother and more reliable operation.

System Architecture

Received: 24-07-2026 | Accepted: 30-08-2026 | Published: 05-09-2026


International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper




The system architecture represents the complete workflow of the Human Following Robot from target detection to automatic movement. The process begins with the surrounding environment containing the target person and possible obstacles. The camera and distance or motion sensors collect information about the person's position, distance, and surrounding objects. The sensor data is sent to the microcontroller for processing and decision-making. The human detection module determines whether the target person is detected within the required range. The distance measurement module calculates the approximate distance between the robot and the target. The obstacle detection module checks the robot's path for objects that may cause a collision. The microcontroller processes all these inputs and determines the appropriate movement command. The motor control module sends signals to the motor driver according to the required direction and speed. The motor driver operates the left and right motors to move the robot forward, backward, or turn. If the target is at a suitable distance, the robot can stop and wait for further movement. The system continuously repeats the sensing and decision-making process to maintain tracking of the target person.

V. Result and Output

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper










Received: 24-07-2026 | Accepted: 30-08-2026 | Published: 05-09-2026

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

7. OBSTACLE DETECTION OUTPUT



8. PERFORMANCE RESULTS

Parameter	Expected Result	Actual Result	Status
Person Detection	Detect person in range	Person detected	PASS
Following Distance	Maintain 1 – 1.5 m	1.25 – 1.40 m	PASS
Angle Tracking	-30° to +30°	-28° to +26°	PASS
Obstacle Detection	Detect & avoid obstacle	Obstacle detected	PASS
Response Time	< 1 second	~ 0.45 second	PASS
Battery Backup	2 – 3 hours	2.4 hours	PASS

VI. Conclusion

The Human Following Robot project successfully demonstrates the development of an autonomous robotic system capable of detecting, tracking, and following a person with minimal human intervention. The system integrates a microcontroller, sensors, camera, motor driver, DC motors, and power supply to achieve automatic movement and target tracking.

The robot continuously receives information about the person's position and distance and adjusts its movement accordingly. It can move forward, turn left, turn right, or stop based on the target's movement. Obstacle detection also helps the robot avoid collisions and navigate safely.

The developed system reduces the need for manual control and can be useful in applications such as luggage transportation, personal assistance, healthcare, warehouses, and service robotics. The combination of sensing and automatic motor control provides a practical solution for human-following applications.

Overall, the project demonstrates the effective application of robotics, embedded systems, sensors, motor control, and human-tracking technology. The system can be further improved by integrating AI-based person recognition, advanced computer vision, LiDAR, GPS, voice commands, and intelligent path planning to achieve more accurate, safe, and reliable human-following performance.

References

[1] Kumar, R. D., Prudhviraj, G., Vijay, K., Kumar, P. S., & Plugmann, P. (2024). Exploring COVID-19 through intensive investigation with supervised machine learning algorithm. In Handbook of Artificial Intelligence and Wearables (pp. 145-158). CRC Press.
[2] Swathi, B., Vijay, K., Sushanth Babu, M., & Dinesh Kumar, R. (2024, November). Machine Learning Techniques in Cloud Based Intrusion Detection. In The International Conference on Artificial Intelligence and Smart Environment (pp. 557-564). Cham: Springer Nature Switzerland.
[3] Sv satyakrishna, shirisha rangu ,bhargavi nalacheruve.(2024) Prospective investigation on colorectal cancer with SMOTE on machine learning Algorithm
[4] Dr.G.Vishnu Murthy, BhargaviNalacheruve 1Professor, Department of computer Science & engineering, Anurag University, TS, India. 2Student, Department of computer Science & engineering, Anurag University, TS, India.

International Journal of
AI ELECTRICAL CIVIL AND MECHANICAL ENGINEERING
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0434 www.zesterapublications.com Original Research Paper

[5] V. N. S. Manaswini, K. K, C. Nigam, S. S. Ali, R. Niranjana, and Suman, "Real-Time Object Detection in Drone Surveillance Using YOLOv5," in Proc. 2025 3rd Int. Conf. IoT, Communication and Automation Technology (ICICAT), Gorakhpur, India, 2025, pp. 1–6, doi: 10.1109/ICICAT68430.2025.11414670.

[6] B. Soundarya, V. N. S. Manaswini, M. Ayyakrishnan, R. D. Kumar, "Contextual Analysis of Big Data Analytics in Intelligent Transportation Frameworks," in Intersection of Artificial Intelligence, Data Science, and Cutting-Edge Technologies: From Concepts to Applications in Smart Environment, Lecture Notes in Networks and Systems, vol. 1353, Cham: Springer, 2025, doi: 10.1007/978-3-031-88304-0_79.

[7] R. D. Kumar, V. N. S.Manaswini, "Applications of blockchain in smart cities: detecting fake documents from land records using blockchain technology," in Blockchain for Smart Cities, Elsevier, 2021, pp. 105–117, doi: 10.1016/B978-0-12-824446-3.00017-X.

[8] Tejavath Veeramma, Badarla Anil, Guguloth Ravinder, "An advanced movie recommender using collaborative filtering and sentiment analysis," International Research Journal of Modernization in Engineering Technology and Science, vol. 7, no. 7, July 2025, doi: 10.56726/IRJMETS81618.

[9] Ravi Kumar Banoth, Ramana Murthy B V, "Automatic crop recommendation system using LightGBM and decision tree machine learning models," Journal of Machine and Computing, vol. 5, no. 1, pp. 343, Jan. 2025, doi: 10.53759/7669/jmc202505026.

[10] Ravi Kumar Banoth, Dr. B.V. Ramana Murthy, "Smart agriculture through IoT and machine learning for analyzing carbon footprints," in Proc. Int. Conf. Computer Science and Communication Engineering (ICCSCE), Apr. 2025.

[11] Ravi Kumar Banoth, B. V. Ramana Murthy, "Soil image classification using transfer learning approach: MobileNetV2 with CNN," SN Computer Science, vol. 5, art. no. 199, 2024, doi: 10.1007/s42979-023-02500-x.