

IoT-Based Smart AgroRobot for Soil Monitoring and AI-Based Crop Prediction

Mr. Soumyaranjan Kandi
Student, Dept. of CSE,
GIFT Autonomous, Bhubaneswar

Mr. Manas Dash
Student, Dept. of CSE,
GIFT Autonomous, Bhubaneswar

Asst.Prof. Meenakshi Moharana
Assistant Professor, Dept. of MCA,
GIFT Autonomous, Bhubaneswar

Abstract— The proposed “IoT-Based Smart AgroRobot for Soil Monitoring and AI-Based Crop Prediction” system is designed to improve modern agricultural practices using IoT technology, machine learning, robotics, and real-time monitoring systems. The system integrates soil moisture sensors, pH sensors, temperature and humidity sensors, ESP32 microcontroller, robotic movement control, and a Flask-based web dashboard to perform intelligent soil monitoring and crop prediction operations. The collected sensor data is analyzed using a machine learning model to predict suitable crops, fertilizer recommendations, and agricultural precautions based on real-time soil conditions. The AgroRobot supports wireless communication through ESP32 hotspot connectivity and enables live dashboard monitoring, robotic movement control, servo motor control, history management, and PDF report generation. The proposed system reduces manual effort, improves monitoring efficiency, and supports precision agriculture through automation and intelligent decision-making. Experimental results demonstrated reliable real-time monitoring, stable communication, successful robotic operation, and accurate AI-based crop prediction. The system can significantly contribute toward smart farming and sustainable agriculture applications.

Keywords— *IoT, Smart Agriculture, ESP32, Machine Learning, Soil Monitoring, AgroRobot, Crop Prediction, Flask Dashboard, PCA9685, Sensors.*

I. INTRODUCTION

Agriculture is one of the most important sectors contributing to economic development, food production, employment generation, and human survival. In many developing countries, agriculture acts as the backbone of the economy and supports the livelihood of millions of farmers. However, traditional agricultural practices mainly depend on manual monitoring, human observation, and conventional farming techniques, which are often inefficient, time-consuming, labor-intensive, and less accurate. Farmers usually rely on experience and visual inspection to monitor soil conditions, irrigation requirements, environmental parameters, and crop health. These traditional approaches may lead to incorrect decision-making, delayed disease detection, poor crop selection, excessive water usage, and reduced agricultural productivity. Therefore, the adoption of modern intelligent technologies in agriculture has become essential for improving farming efficiency and achieving sustainable agricultural development.

The rapid advancement of technologies such as Internet of Things (IoT), Artificial Intelligence (AI), Machine Learning (ML), robotics, cloud computing, and embedded systems has

introduced new possibilities for smart agriculture and precision farming applications. These advanced technologies enable automated monitoring, intelligent decision-making, real-time environmental analysis, robotic automation, and data-driven agricultural management. IoT technology allows multiple sensors and smart devices to communicate and exchange real-time information over wireless networks. Machine learning algorithms analyze agricultural data and generate intelligent predictions and recommendations. Robotics technologies help automate monitoring and field operations, thereby reducing human effort and improving operational efficiency.

Smart agriculture systems have become increasingly popular because they provide accurate monitoring and intelligent agricultural management solutions. Modern agricultural monitoring systems use various sensors for collecting environmental and soil-related parameters such as soil moisture, temperature, humidity, pH level, rainfall, and nutrient conditions. These parameters are important for crop growth, irrigation management, fertilizer selection, and disease prevention. By continuously monitoring these environmental conditions, farmers can make better decisions regarding crop cultivation and resource management.

The proposed “IoT-Based Smart AgroRobot for Soil Monitoring and AI-Based Crop Prediction” system is designed as an intelligent agricultural automation platform that combines IoT technology, machine learning, robotics, wireless communication, and web-based monitoring into a single integrated system. The primary objective of the proposed system is to automate soil monitoring and crop prediction operations using real-time sensor data and intelligent analysis techniques. The system aims to reduce manual monitoring effort, improve agricultural productivity, support precision farming, and provide accurate crop recommendations according to soil conditions.

The proposed system consists of both hardware and software modules working together for intelligent agricultural monitoring. The hardware implementation includes ESP32 microcontroller, soil moisture sensor, pH sensor, DHT22 temperature and humidity sensor, L298N motor driver module, PCA9685 servo driver module, servo motors, DC motors, and rechargeable battery modules. The ESP32 microcontroller acts as the central control and communication unit of the AgroRobot system. It continuously collects environmental and soil data from connected sensors and transmits the collected information to the Flask-based dashboard through hotspot

communication. The soil moisture sensor measures the water content present in agricultural soil and helps determine irrigation requirements and soil conditions. The pH sensor monitors soil acidity and alkalinity levels, which are important factors affecting crop growth and fertilizer recommendations. The DHT22 sensor measures environmental temperature and humidity conditions for agricultural monitoring and environmental analysis. These sensors continuously provide real-time environmental information that is further analyzed by the machine learning module for intelligent crop prediction.

The robotic movement architecture of the AgroRobot system is implemented using DC motors controlled through the L298N motor driver module. The robot can move in forward, backward, left, and right directions according to dashboard control commands. The PCA9685 servo driver module controls multiple servo motors responsible for sensor positioning and flexible monitoring operations. The robotic system improves field monitoring efficiency and enables soil analysis at different locations within agricultural land.

The software implementation of the proposed system is developed using Python programming language and Flask web framework. The Flask-based dashboard provides an interactive user interface for live sensor monitoring, robotic movement control, servo control operations, crop prediction analysis, report generation, and history management functionalities. The dashboard receives real-time sensor readings from the ESP32 controller and displays environmental conditions to the user in graphical and numerical formats.

Machine learning plays a major role in the proposed smart agriculture system. The machine learning model analyzes soil moisture, pH, temperature, and humidity parameters for predicting suitable crops according to soil conditions. The prediction system also provides fertilizer recommendations and agricultural precautions for improving crop productivity and soil quality management. The use of machine learning algorithms improves prediction accuracy and supports intelligent agricultural decision-making processes.

The proposed system also includes report generation and history management functionalities for maintaining agricultural analysis records. The system stores previous analysis data in JSON format and generates professional PDF reports containing sensor readings, crop prediction results, fertilizer recommendations, and agricultural precautions. These reports help users maintain agricultural documentation for future analysis and monitoring purposes.

One of the major advantages of the proposed system is its hotspot communication architecture using ESP32. Unlike cloud-dependent systems requiring continuous internet connectivity, the proposed system creates a local wireless communication network that enables direct communication between the AgroRobot and the Flask dashboard without requiring external internet access. This makes the system suitable for deployment in remote agricultural environments where internet connectivity may not always be available.

The proposed “IoT-Based Smart AgroRobot for Soil Monitoring and AI-Based Crop Prediction” system represents an important step toward intelligent farming and sustainable

agriculture. The integration of IoT technology, robotics, machine learning, and web-based monitoring improves monitoring accuracy, reduces manual effort, supports precision agriculture, and enhances agricultural productivity. The system provides a low-cost, scalable, and intelligent solution for modern smart farming applications and demonstrates the practical implementation of Artificial Intelligence and IoT technologies in agriculture.

II. LITERATURE SURVEY

Agriculture has undergone significant technological transformation over the past few decades due to the integration of Internet of Things (IoT), Artificial Intelligence (AI), Machine Learning (ML), robotics, wireless communication, and sensor technologies. Researchers across the world have developed various smart agriculture systems for improving agricultural productivity, reducing manual effort, optimizing resource utilization, and supporting intelligent decision-making processes. The growing demand for sustainable agriculture and precision farming has encouraged the development of automated agricultural monitoring systems capable of collecting real-time environmental data and generating intelligent agricultural recommendations.

One of the major research areas in smart agriculture is IoT-based environmental monitoring systems. These systems use multiple sensors such as soil moisture sensors, temperature sensors, humidity sensors, pH sensors, rainfall sensors, and nutrient sensors for collecting environmental and soil-related data from agricultural fields. The collected sensor data is transmitted wirelessly to monitoring servers or cloud platforms for analysis and visualization. Researchers have demonstrated that IoT-based agricultural monitoring systems can improve irrigation management, reduce water wastage, and support efficient crop cultivation practices.

Several researchers have developed wireless sensor network (WSN)-based smart agriculture systems for remote agricultural monitoring. These systems mainly focus on monitoring environmental conditions and automating irrigation control processes. Wireless communication technologies such as WiFi, ZigBee, Bluetooth, GSM, and LoRa are commonly used for transmitting sensor data to remote servers or dashboards. Although these systems improve monitoring efficiency, many existing systems mainly focus only on environmental monitoring and lack intelligent crop prediction and robotic automation capabilities.

Machine learning and Artificial Intelligence technologies have also been widely applied in agriculture for crop prediction, disease detection, yield estimation, fertilizer recommendation, and soil analysis applications. Researchers have developed machine learning models using algorithms such as Decision Tree, Random Forest, Support Vector Machine (SVM), K-Nearest Neighbor (KNN), Naive Bayes, and Artificial Neural Networks for analyzing agricultural datasets and generating intelligent predictions. These machine learning systems improve agricultural decision-making and help farmers select suitable crops according to environmental and soil conditions.

Crop prediction systems based on machine learning mainly

analyze environmental parameters such as soil moisture, pH level, temperature, humidity, rainfall, and nutrient conditions for predicting suitable crops. Some systems also provide fertilizer recommendations and agricultural precautions for improving farming productivity. Although machine learning improves prediction accuracy, many existing crop prediction systems depend on manual data entry rather than real-time sensor monitoring. This reduces automation efficiency and limits real-time agricultural analysis capability.

Researchers have also developed image processing and computer vision-based agricultural systems for crop disease detection and plant health monitoring. These systems analyze crop leaf images using deep learning algorithms such as Convolutional Neural Networks (CNNs) for identifying diseases and pest infections. While these systems improve disease detection accuracy, they generally focus only on image analysis and do not integrate real-time soil monitoring and robotic automation functionalities.

Robotics has become another important research area in modern agriculture. Agricultural robots are being developed for crop monitoring, harvesting, irrigation, spraying, seed planting, and environmental analysis operations. Robotic systems improve agricultural automation and reduce human labor requirements. Some robotic agriculture systems use autonomous navigation and GPS-based movement control for large-scale field monitoring applications. However, many robotic systems are expensive, complex, and difficult to deploy in small-scale agricultural environments.

Several smart farming systems also use cloud computing for storing agricultural data and enabling remote monitoring functionalities. Cloud-based agriculture systems provide large-scale data storage, multi-user accessibility, remote monitoring, and data analytics capabilities. However, cloud-dependent systems require continuous internet connectivity and may not operate efficiently in rural or remote agricultural areas with poor network availability.

Many existing agricultural systems also suffer from limitations such as high implementation cost, dependency on internet connectivity, limited real-time monitoring capability, lack of integrated robotics support, absence of intelligent prediction systems, and complex operational architecture. Most systems focus on either environmental monitoring or crop prediction separately rather than integrating all functionalities into a single smart agriculture platform.

The proposed “IoT-Based Smart AgroRobot for Soil Monitoring and AI-Based Crop Prediction” system is developed to overcome these limitations by integrating IoT technology, machine learning, robotics, wireless communication, and dashboard-based monitoring into a unified agricultural automation platform. Unlike traditional monitoring systems, the proposed system combines real-time sensor monitoring, robotic movement control, machine learning-based crop prediction, hotspot communication, report generation, and dashboard management functionalities into a single intelligent solution.

The proposed system uses ESP32 microcontroller for sensor monitoring, robotic control, and wireless hotspot

communication. The integration of hotspot communication removes dependency on external internet connectivity and improves system usability in remote agricultural environments. The machine learning module analyzes real-time soil and environmental conditions for generating crop prediction results and fertilizer recommendations. The robotic movement architecture improves field monitoring flexibility and enables intelligent agricultural automation.

The Flask-based dashboard provides an interactive interface for live monitoring, robotic control, report generation, and history management operations. The system also supports PDF report generation and JSON-based history management for maintaining agricultural analysis records. The use of low-cost hardware components such as ESP32, L298N motor driver, PCA9685 servo driver, and open-source software technologies makes the proposed system affordable, scalable, and suitable for both small-scale and large-scale agricultural applications.

Overall, the literature survey indicates that although many IoT-based smart agriculture systems have been developed, there is still a need for integrated agricultural automation systems that combine real-time monitoring, machine learning prediction, robotics, wireless communication, and intelligent dashboard management into a single platform. The proposed system addresses these requirements and contributes toward modern smart farming and precision agriculture applications using IoT and Artificial Intelligence technologies.

III. PROPOSED SYSTEM

The proposed “IoT-Based Smart AgroRobot for Soil Monitoring and AI-Based Crop Prediction” system is developed as an intelligent smart agriculture solution by integrating Internet of Things (IoT), robotics, machine learning, wireless communication, and web-based monitoring technologies into a unified agricultural automation platform. The main objective of the proposed methodology is to automate soil analysis, environmental monitoring, robotic movement, crop prediction, and agricultural recommendation processes using real-time sensor data and Artificial Intelligence techniques. The proposed system is designed to improve agricultural efficiency, reduce manual monitoring effort, and support precision farming applications through intelligent automation.

The complete system architecture is divided into multiple interconnected hardware and software modules that work together to perform soil monitoring and crop prediction operations. The hardware section mainly consists of ESP32 microcontroller, soil moisture sensor, pH sensor, DHT22 temperature and humidity sensor, L298N motor driver module, PCA9685 servo driver module, servo motors, DC motors, and rechargeable battery modules. The ESP32 microcontroller acts as the central processing and communication unit of the AgroRobot system. It continuously collects sensor data, controls robotic movement operations, and communicates with the Flask-based dashboard using local hotspot communication.


The soil moisture sensor measures the water content present in agricultural soil and helps in determining irrigation conditions

and soil quality. The pH sensor monitors the acidity and alkalinity level of soil, which is an important parameter for selecting suitable crops and fertilizer recommendations. The DHT22 sensor measures atmospheric temperature and humidity conditions for environmental monitoring and agricultural analysis. The collected sensor values are continuously processed by the ESP32 controller and transmitted wirelessly to the Flask dashboard interface. The robotic movement section of the AgroRobot system is implemented using DC motors connected through the L298N motor driver module. The AgroRobot can move in forward, backward, left, and right directions according to dashboard control commands. The PCA9685 servo driver controls multiple servo motors responsible for sensor positioning and robotic monitoring operations. The robotic system enables efficient soil analysis at different field locations and improves monitoring flexibility.

The software implementation of the proposed system consists of Flask web framework, machine learning crop prediction module, dashboard interface, history management system, and PDF report generation system. The Flask dashboard provides an interactive interface for displaying live sensor readings, controlling robotic movement, operating servo motors, performing soil analysis, and generating agricultural reports. The machine learning model analyzes the collected soil parameters and predicts suitable crops according to soil conditions. The prediction system also generates fertilizer recommendations and agricultural precautions for improving farming productivity and soil quality.

The proposed methodology begins with real-time sensor data acquisition from agricultural land. The ESP32 controller reads sensor values through analog and digital pins and sends the data to the Flask server through hotspot communication. The machine learning module processes the sensor data and generates intelligent agricultural recommendations. The generated reports are stored in JSON format and can also be downloaded as professional PDF reports for future agricultural analysis and documentation purposes.

The integration of IoT technology, machine learning algorithms, robotics, and real-time dashboard monitoring enables the proposed system to improve monitoring accuracy, reduce manual effort, increase prediction efficiency, and support intelligent agricultural decision-making for smart farming applications.



IV. SYSTEM ARCHITECTURE

The system architecture of the proposed “IoT-Based Smart AgroRobot for Soil Monitoring and AI-Based Crop Prediction” system is designed using a modular and layered architecture where hardware modules, communication systems, machine learning models, robotic systems, and web technologies are integrated into a single intelligent agricultural platform. The architecture mainly consists of sensor monitoring modules, ESP32 controller unit, robotic movement system, wireless communication layer, Flask-based dashboard server, machine learning crop prediction system, history management module, and PDF report generation module.

The sensor layer of the system contains multiple sensors responsible for collecting real-time agricultural data from the environment. The soil moisture sensor measures water content present in the soil and helps in monitoring irrigation conditions. The pH sensor measures soil acidity and alkalinity levels for determining suitable crop conditions. The DHT22 sensor measures environmental temperature and humidity parameters. These sensors continuously collect environmental data and send the readings to the ESP32 controller for processing and communication operations.

The ESP32 microcontroller acts as the central control unit of the AgroRobot system. It performs sensor data acquisition, wireless communication, robotic control, and dashboard synchronization operations. The ESP32 controller receives sensor values through analog and digital input pins and processes the collected data in real time. The built-in WiFi capability of ESP32 creates a local hotspot communication network that allows the Flask dashboard to connect directly with the AgroRobot system without requiring external internet connectivity. This communication architecture improves system reliability and enables deployment in remote agricultural environments.


The robotic movement architecture of the system consists of L298N motor driver module, DC motors, PCA9685 servo driver module, and servo motors. The L298N driver controls the movement of DC motors responsible for AgroRobot mobility. The robot supports forward, backward, left, and right movement operations controlled through dashboard commands. The PCA9685 servo driver controls servo motors responsible for sensor positioning and flexible agricultural monitoring

operations. This robotic movement architecture improves field coverage and monitoring flexibility.

The Flask-based dashboard acts as the software control and monitoring layer of the proposed architecture. The dashboard receives live sensor readings from the ESP32 controller and displays real-time soil and environmental conditions to the user. The dashboard also provides robotic movement controls, servo controls, soil analysis operations, report generation functionalities, and history management options. Users can monitor agricultural conditions and control the AgroRobot directly through the dashboard interface.

The machine learning layer of the proposed system analyzes collected soil and environmental parameters for generating intelligent crop prediction results. The trained machine learning model predicts suitable crops according to soil conditions and generates fertilizer recommendations and agricultural precautions. The generated prediction results are stored in JSON format and can be converted into PDF reports for future analysis and documentation.

The integrated architecture of the proposed system enables real-time soil monitoring, robotic automation, machine learning-based crop prediction, dashboard communication, and intelligent agricultural decision-making within a single smart agriculture platform. The architecture improves precision farming efficiency and supports sustainable agricultural practices using IoT and Artificial Intelligence technologies.



V. HARDWARE AND SOFTWARE IMPLEMENTATION

The hardware and software implementation of the proposed “IoT-Based Smart AgroRobot for Soil Monitoring and AI-Based Crop Prediction” system is designed using multiple integrated modules that work together for performing intelligent agricultural monitoring and automation operations. The implementation process mainly includes sensor integration, robotic movement control, wireless communication, machine learning-based crop prediction, dashboard monitoring, and report generation functionalities. The integration of both hardware and software technologies enables the proposed system to perform real-time monitoring and intelligent agricultural analysis efficiently.

The hardware implementation mainly consists of ESP32 microcontroller, DHT22 temperature and humidity sensor, soil moisture sensor, pH sensor, L298N motor driver module,

PCA9685 servo driver module, servo motors, DC motors, and battery power supply modules. The ESP32 microcontroller acts as the central control unit of the AgroRobot system. It is responsible for reading sensor data, controlling robotic movement, managing wireless communication, and sending live sensor readings to the Flask dashboard through WiFi hotspot communication. The built-in WiFi capability of ESP32 enables direct communication between the AgroRobot system and the web dashboard without requiring external internet connectivity. The DHT22 sensor continuously monitors environmental temperature and humidity conditions required for agricultural analysis. The soil moisture sensor measures the water content present in agricultural soil and helps in determining irrigation conditions and soil quality. The pH sensor measures soil acidity and alkalinity levels, which are important parameters for crop prediction and fertilizer recommendation processes. These sensors continuously collect real-time environmental data and transmit the readings to the ESP32 controller for processing operations.

The robotic movement system of the AgroRobot is implemented using DC motors connected through the L298N motor driver module. The robot supports forward, backward, left, and right movement operations controlled through dashboard commands. The L298N driver controls motor direction and speed operations efficiently. The PCA9685 servo driver module controls servo motors responsible for sensor positioning and flexible monitoring operations. The servo system improves agricultural monitoring flexibility by enabling accurate sensor movement and positioning across different field locations.

The software implementation of the proposed system is developed using Python programming language and Flask web framework. The Flask dashboard acts as the main user interface of the system and provides live sensor monitoring, robotic movement control, servo control, crop prediction operations, report generation, and history management functionalities. The dashboard continuously receives live sensor readings from the ESP32 controller and displays real-time agricultural conditions to the user.

The machine learning implementation analyzes soil moisture, pH, temperature, and humidity values for generating intelligent crop prediction results. The trained machine learning model predicts suitable crops according to soil conditions and also generates fertilizer recommendations and agricultural precautions. The generated analysis results are stored in JSON format and can also be downloaded as professional PDF reports for future agricultural analysis and documentation purposes. The integration of hardware sensors, robotic systems, wireless communication modules, machine learning algorithms, and web-based dashboard technologies enables the proposed AgroRobot system to support intelligent agricultural monitoring, automation, precision farming, and smart decision-making operations efficiently.

VI. RESULTS AND DISCUSSION

The proposed “IoT-Based Smart AgroRobot for Soil Monitoring and AI-Based Crop Prediction” system was successfully implemented and tested under different

agricultural monitoring conditions. The system effectively performed real-time soil analysis, environmental monitoring, robotic movement control, crop prediction, fertilizer recommendation, dashboard communication, and report generation operations. The integration of IoT technology, machine learning algorithms, robotics, and web-based monitoring enabled the system to achieve intelligent agricultural automation and precision farming functionalities efficiently.

The sensor monitoring system successfully collected real-time environmental and soil parameters using DHT22 temperature and humidity sensor, soil moisture sensor, and pH sensor modules. The DHT22 sensor continuously monitored atmospheric temperature and humidity conditions and transmitted live readings to the ESP32 controller. The soil moisture sensor accurately measured water content present in agricultural soil, while the pH sensor monitored soil acidity and alkalinity levels required for crop prediction analysis. The collected sensor readings were processed by the ESP32 controller and transmitted wirelessly to the Flask-based dashboard through hotspot communication.

The Flask dashboard successfully displayed live sensor readings and continuously updated real-time agricultural conditions without requiring external internet connectivity. The dashboard interface provided a user-friendly environment for monitoring soil parameters, controlling robotic movement, operating servo motors, generating crop predictions, viewing historical data, and downloading analysis reports. The dashboard communication system demonstrated stable wireless connectivity between ESP32 and Flask server using hotspot communication architecture. The robotic movement section of the AgroRobot system operated successfully using DC motors connected through the L298N motor driver module. The robot responded accurately to movement commands such as forward, backward, left, and right directions through dashboard control operations. The PCA9685 servo driver module successfully controlled servo motor movement for sensor positioning and flexible monitoring operations. The robotic system improved field monitoring efficiency by enabling movement across different agricultural locations.

The machine learning crop prediction module successfully analyzed collected soil and environmental parameters and generated intelligent crop prediction results according to soil conditions. The prediction system also generated fertilizer recommendations and agricultural precautions for improving crop productivity and soil quality. The prediction accuracy was improved by using real-time sensor values instead of static manual input parameters.

The history management and PDF report generation system successfully stored agricultural analysis data in JSON format and generated professional PDF reports containing sensor readings, crop prediction results, fertilizer recommendations, and agricultural precautions. The generated reports improved agricultural documentation and enabled future analysis and monitoring operations.

The overall system testing demonstrated reliable communication, stable sensor monitoring, accurate robotic

control, efficient dashboard operation, and successful machine learning prediction functionalities. The proposed AgroRobot system significantly reduced manual monitoring effort, improved agricultural analysis efficiency, and supported intelligent decision-making for smart farming applications. The implementation results confirmed that the proposed system can effectively contribute toward precision agriculture, agricultural automation, and sustainable smart farming practices using IoT and Artificial Intelligence technologies.




Fig 6.1 Output

VII. ADVANTAGE OF PROPOSED SYSTEM

The proposed “IoT-Based Smart AgroRobot for Soil Monitoring and AI-Based Crop Prediction” system provides multiple advantages over traditional agricultural monitoring and manual farming methods. The integration of Internet of Things (IoT), robotics, machine learning, wireless communication, and dashboard technologies enables the system to perform intelligent agricultural monitoring and automation operations efficiently. The proposed system improves agricultural productivity, reduces manual effort, enhances monitoring accuracy, and supports precision farming applications through real-time data analysis and intelligent decision-making functionalities. One of the major advantages of the proposed system is real-time soil and environmental monitoring. The integration of soil moisture sensor, pH sensor, and DHT22 temperature and humidity sensor enables continuous monitoring of important agricultural parameters. The system continuously collects live sensor readings and displays the values on the Flask dashboard in real time. This helps farmers and agricultural users monitor environmental conditions efficiently and take immediate corrective actions whenever required.

Another important advantage of the system is intelligent crop prediction using machine learning algorithms. The machine learning model analyzes real-time soil and environmental conditions and predicts suitable crops according to soil quality parameters. The prediction system also provides fertilizer recommendations and agricultural precautions for improving crop productivity and maintaining soil health. This intelligent recommendation system supports precision agriculture and improves farming decision-making processes.

The robotic movement and automation capability of the

AgroRobot system is another significant advantage. The robot can move in forward, backward, left, and right directions through dashboard control operations. The robotic movement system improves field monitoring flexibility and enables efficient agricultural data collection from different field locations. The PCA9685 servo driver also enables flexible sensor positioning for accurate monitoring operations.

The Flask-based dashboard interface provides a user-friendly platform for agricultural monitoring and robotic control. The dashboard displays live sensor readings, crop prediction results, robotic control options, analysis reports, and historical data management functionalities. The hotspot communication capability of ESP32 allows direct communication between the AgroRobot system and the dashboard without requiring external internet connectivity. This improves system reliability and enables deployment in remote agricultural environments where internet connectivity may not be available.

The PDF report generation and history management functionalities improve agricultural documentation and data storage operations. The system stores previous analysis results in JSON format and generates professional PDF reports containing sensor readings, crop prediction results, fertilizer recommendations, and agricultural precautions. These reports help users maintain agricultural records for future monitoring and analysis purposes.

The proposed system also reduces manual monitoring effort and saves time by automating soil analysis and crop prediction operations. Traditional agricultural monitoring methods mainly depend on manual inspection and laboratory testing, which are time-consuming and less efficient. The proposed smart agriculture system automates these operations using real-time sensors and machine learning technologies, thereby improving efficiency and reducing operational complexity.

Another major advantage of the proposed system is its low-cost and scalable architecture. The system is developed using low-cost hardware components such as ESP32, sensors, motor drivers, and open-source software technologies. This makes the system affordable and suitable for small-scale and large-scale agricultural applications. The modular architecture of the system also enables future expansion and integration of additional sensors and intelligent technologies.

Overall, the proposed smart AgroRobot system provides an efficient, intelligent, scalable, and cost-effective solution for modern agricultural monitoring, automation, and precision farming applications using IoT and Artificial Intelligence technologies.

VIII. FUTURE SCOPE

The proposed "IoT-Based Smart AgroRobot for Soil Monitoring and AI-Based Crop Prediction" system provides an intelligent and efficient solution for modern smart agriculture applications. Although the current implementation successfully performs real-time soil monitoring, robotic movement control, machine learning-based crop prediction, dashboard communication, and report generation operations, there is significant scope for future enhancement and technological advancement. The integration of additional

intelligent technologies and automation functionalities can further improve system performance, scalability, accuracy, and agricultural usability.

One of the major future enhancements of the proposed system is the development of a dedicated mobile application for Android and iOS platforms. A mobile application can provide farmers and agricultural users with direct access to live sensor monitoring, robotic control, crop prediction, and report generation functionalities through smartphones. Mobile-based agricultural monitoring can improve accessibility and allow users to operate the AgroRobot system efficiently from agricultural fields without requiring laptops or desktop systems.

Another important future improvement is cloud integration and remote monitoring capability. Currently, the proposed system mainly uses ESP32 hotspot communication for local wireless connectivity. In future versions, cloud-based communication architecture can be integrated for enabling remote agricultural monitoring and data synchronization over the internet. Cloud storage can improve large-scale agricultural data management, multi-user accessibility, real-time synchronization, and long-term agricultural analysis operations.

The machine learning module of the proposed system can also be improved further by using larger and more diverse agricultural datasets. The current prediction model mainly analyzes soil moisture, pH, temperature, and humidity parameters for crop prediction operations. Future enhancements may include advanced deep learning algorithms, large-scale agricultural datasets, weather forecasting integration, and region-specific crop analysis for improving prediction accuracy and recommendation quality.

Another valuable future enhancement is the integration of additional agricultural sensors such as NPK sensors, rainfall sensors, sunlight intensity sensors, gas sensors, and environmental monitoring modules. These additional sensors can provide more detailed soil and environmental analysis and improve intelligent agricultural decision-making capabilities. The integration of image processing and computer vision technologies can also enable crop disease detection and plant health monitoring functionalities.

The robotic movement architecture of the AgroRobot system can further be upgraded into a fully autonomous agricultural robot using GPS modules, ultrasonic sensors, obstacle detection systems, and AI-based navigation technologies. Autonomous navigation capability will allow the robot to move automatically across agricultural fields without manual dashboard control operations. This enhancement can improve monitoring efficiency and support large-scale agricultural automation applications.

Future versions of the system can also integrate automated irrigation control mechanisms using relay modules and smart water management technologies. The system can automatically activate irrigation systems according to soil moisture conditions and environmental requirements. This can help reduce water wastage and improve irrigation efficiency in agricultural environments.

Another important future enhancement is the implementation of

edge AI processing and offline prediction capability. Future systems can perform crop prediction and agricultural analysis directly on edge devices such as ESP32 or embedded AI modules without depending on external servers. This can improve processing speed, reduce latency, and support deployment in remote agricultural regions with limited internet connectivity.

Multi-language dashboard support can also be implemented using regional languages such as Hindi, Odia, Bengali, and other local languages to improve accessibility for farmers from different regions. Advanced graphical analytics, historical data visualization, and automated agricultural advisory systems can further improve the overall user experience and intelligent farming capabilities.

Overall, the future enhancements of the proposed system can transform the AgroRobot into a fully autonomous, intelligent, scalable, and highly efficient precision agriculture platform capable of supporting modern smart farming and sustainable agricultural development using IoT, Artificial Intelligence, robotics, and cloud technologies.

CONCLUSION

The proposed “IoT-Based Smart AgroRobot for Soil Monitoring and AI-Based Crop Prediction” system has been successfully designed and implemented as an intelligent smart agriculture solution by integrating Internet of Things (IoT), robotics, machine learning, and web-based monitoring technologies into a unified agricultural automation platform. The system effectively performs real-time soil monitoring, environmental analysis, robotic movement control, crop prediction, fertilizer recommendation, dashboard communication, and report generation operations. The integration of advanced technologies enables the proposed system to support intelligent agricultural decision-making and precision farming applications efficiently.

The developed system successfully combines hardware and software technologies for achieving automated agricultural monitoring and analysis. The hardware implementation includes ESP32 microcontroller, soil moisture sensor, pH sensor, DHT22 temperature and humidity sensor, L298N motor driver module, PCA9685 servo driver module, servo motors, DC motors, and battery power supply systems. The ESP32 controller acts as the central processing unit of the AgroRobot system and performs sensor monitoring, robotic movement control, wireless communication, and dashboard synchronization operations. The hotspot communication capability of ESP32 allows direct communication between the AgroRobot system and the Flask dashboard without requiring external internet connectivity.

The sensor monitoring system successfully collects real-time soil and environmental parameters required for agricultural analysis. The soil moisture sensor monitors soil water content, while the pH sensor measures soil acidity and alkalinity levels for crop prediction operations. The DHT22 sensor continuously measures environmental temperature and humidity conditions for improving agricultural monitoring accuracy. The collected sensor data is processed and transmitted wirelessly to the Flask dashboard through hotspot

communication architecture.

The robotic movement section of the AgroRobot system operates successfully using DC motors connected through the L298N motor driver module. The robot responds accurately to movement commands such as forward, backward, left, and right directions through dashboard control operations. The PCA9685 servo driver controls servo motors responsible for sensor positioning and flexible monitoring operations. The robotic movement architecture improves field monitoring flexibility and enables efficient agricultural data collection from different field locations.

The Flask-based dashboard interface successfully provides live monitoring and intelligent control functionalities for the proposed system. The dashboard displays real-time sensor readings, crop prediction results, robotic movement controls, servo control operations, history management functionalities, and PDF report generation options. The machine learning prediction module analyzes collected soil parameters and generates intelligent crop prediction results along with fertilizer recommendations and agricultural precautions according to soil conditions.

The implementation and testing results confirmed that the proposed system operates efficiently and reliably under different agricultural monitoring conditions. The integration of IoT technology, machine learning algorithms, robotics, and dashboard communication significantly reduces manual monitoring effort, improves monitoring accuracy, supports intelligent agricultural analysis, and enhances farming productivity. The generated PDF reports and history management functionalities also improve agricultural documentation and future monitoring operations.

Although the proposed system has certain limitations related to sensor calibration, communication range, and large-scale deployment, these limitations can be improved through future enhancements such as cloud integration, autonomous navigation, advanced AI processing, image-based crop disease detection, automated irrigation systems, and mobile application support.

In conclusion, the proposed “IoT-Based Smart AgroRobot for Soil Monitoring and AI-Based Crop Prediction” system represents an important step toward intelligent agriculture and sustainable smart farming practices. The system successfully demonstrates the practical implementation of IoT, Artificial Intelligence, robotics, and web technologies for agricultural automation and precision farming applications. The proposed system has strong potential for future expansion and can significantly contribute toward modern agricultural development and smart farming transformation.

REFERENCES

- [1] M. K. Kakhani, S. Kakhani and S. R. Biradar, “Research Issues in Big Data Analytics,” *International Journal of Application or Innovation in Engineering & Management*, vol. 2, no. 8, pp. 228-232, 2015.
- [2] A. Gandomi and M. Haider, “Beyond the Hype: Big Data Concepts, Methods, and Analytics,” *International Journal of*

Information Management, vol. 35, no. 2, pp. 137-144, 2015.

[3] T. K. Das and P. M. Kumar, "Big Data Analytics: A Framework for Unstructured Data Analysis," International Journal of Engineering and Technology, vol. 5, no. 1, pp. 153-156, 2013.

[4] I. A. T. Hashem et al., "The Rise of Big Data on Cloud Computing: Review and Open Research Issues," Information Systems, vol. 47, pp. 98-115, 2014.

[5] N. Mishra, C. Lin and H. Chang, "A Cognitive Adopted Framework for IoT Big Data Management and Knowledge Discovery Perspective," International Journal of Distributed Sensor Networks, 2015.

[6] X. Y. Chen and Z. G. Jin, "Research on Key Technology and Applications for Internet of Things," Physics Procedia, vol. 33, pp. 561-566, 2012.

[7] D. P. Acharjya, S. Dehuri and S. Sanyal, Computational Intelligence for Big Data Analysis, Springer International Publishing, 2015.

[8] H. Zhu, Z. Xu and Y. Huang, "Research on the Security Technology of Big Data Information," International Conference on Information Technology and Management Innovation, 2015.

[9] S. R. Nandurkar, V. R. Thool and R. C. Thool, "Design and Development of Precision Agriculture System Using Wireless Sensor Network," IEEE International Conference on Automation, Control, Energy and Systems, pp. 1-6, 2014.

[10] R. Kamilaris and A. Prenafeta-Boldú, "Deep Learning in Agriculture: A Survey," Computers and Electronics in Agriculture, vol. 147, pp. 70-90, 2018.

[11] J. Burrell, T. Brooke and R. Beckwith, "Vineyard Computing: Sensor Networks in Agricultural Production," IEEE Pervasive Computing, vol. 3, no. 1, pp. 38-45, 2004.

[12] P. Rajalakshmi and S. Devi Mahalakshmi, "IoT Based Crop-Field Monitoring and Irrigation Automation," Proceedings of the 10th International Conference on Intelligent Systems and Control, pp. 1-6, 2016.