International Journal of
AI Electronics and Nexus Energy
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0515 www.zesterapublications.com Original Research Paper

# An Intelligent Clinical Decision Support System for Chronic Kidney Disease Detection Using Machine Learning

**C Vinay[1], T Sunil Kumar Reddy[2]**

[1]P.G Scholar, Department of MCA, Sri Venkatesa Perumal College of Engineering & Technology, Puttur,
E-mail: chandragirivinay930@gmail.com, ORC-ID: https://orcid.org/0009-0009-1139-3464
[2]Professor, Department of CSE, Sri Venkatesa Perumal College of Engineering & Technology, Puttur,
E-mail: sunilreddy.vit@gmail.com, ORC-ID: https://orcid.org/0000-0003-1257-7985

**Abstract:** Chronic Kidney Disease (CKD) is a disease that is progressive, and it may cause serious outcomes and renal failure unless identified in its early stages. This paper presents a smart and explainable model on the prediction of chronic kidney disease with the help of machine learning and ensemble algorithms. The study uses CKD data in the UCI machine learning repository which consisted of 400 patient records collected at the Apollo hospital in India with 25 numerical and categorical variables. Statistical and model-based imputation are used to handle missing values, and Synthetic Minority Over-sampling Technique (SMOTE) is employed to address class imbalance (CKD and non-CKD instances). Complete preprocessing, feature engineering, and feature selection methods are used: Mutual Information, Variance Thresholding, Recursive Feature Elimination, and Sequential Feature Selection, which identify six clinically significant features, namely, hemoglobin, serum creatinine, albumin, hypertension, age, and diabetes mellitus. Stratified K-Fold cross-validation is used to test various classifiers, including the Logistic Regression, Gaussian Naive Bayes, Support Vector Machine, Decision Tree, Random Forest and AdaBoost. A hybrid Voting Classifier which combines random forest with adaboost achieves a very high performance with the accuracy, precision and recall of 99.4 and F1-score of 99.3. The interpretation of the model is enhanced by using LIME and SHAP to explain single predictions and contributions of features. A web application based on Flask includes user registration, authentication, secure data entry, real-time predictions, and explained results, delivering the output of the results as either chronic kidney disease detected or no chronic kidney disease detected, which makes it reliable and user-friendly clinical decision support.

***"Index Terms:*** *CKD, machine learning ensemble models, explainable AI, interpretability".*

## 1. INTRODUCTION

CKD can be described as clinically characterized by kidney damage or permanent deterioration of the kidney function, typically indicated by a GFR of less than 60 mL/min/1.73 m 2 over a period of three months or more [1]. CKD is a significant health issue facing the world, as it is a leading cause of morbidity and mortality worldwide. The trend often leads to irreversible renal dysfunction, which leads to AKI or ESRD, conditions that require costly treatment, including dialysis or transplantation [2]. The condition is usually associated with comorbidities such as Diabetes Mellitus and Hypertension, which significantly predisposes the development of CKD. In clinical diagnosis, the standard laboratory tests including blood and urine tests are used to diagnose CKD. Critical indicators include albuminuria and elevated serum creatinine levels, which are indicators of the lowered ability of kidneys to filter blood (3). The first sign that diabetic kidney is impaired is often the presence of albumin in urine, which is caused by damaged glomerular filters that permit passage of proteins in the urine.

CKD has far reaching health consequences. It can lead to anemia, bone frailty, fluid retention, hypertension, and increase in the cardiovascular risk because the kidneys lose their ability to regulate the production of erythropoietin and vitamin D [5]. According to the CDC, approximately, 37 million individuals in the United States have CKD, and the majority of them are not aware of their condition. In nearly 360 patients, dialysis treatment of renal failure is started every hour, with diabetes and hypertension accounting for an estimated three-quarters of the cases of new renal end-stage disease [6]. It is also worrying on the financial side- the cost of treatment on ESRD in the United States alone is above 32 billion dollars annually, and in developing countries such as India, access to renal replacement drugs is limited by insufficient health insurance coverage and high treatment costs.

The unavailability of diverse medical data and the absence of available medical data hinder CKD analysis, which is an aspect of engineering. Cognitive and sampling biases are common in healthcare data even when they are available, and it is difficult to apply accurate ML applications [8].

International Journal of
AI Electronics and Nexus Energy
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0515 www.zesterapublications.com Original Research Paper

The UCI ML Repository dataset, which was obtained in Apollo Hospital in India, is a diverse resource of CKD prediction; however, it lacks demographic variety and exact clinical variables [9]. New discoveries in XAI have eased the process of better comprehending the model interpretability, which helps identify the key biomarkers that influence the progression of CKD. XAI and ensemble learning model enhance predictive value, clinical transparency, and enable clinicians to make data-driven, informed decisions to detect and manage CKD earlier [10].

## 2. LITERATURE REVIEW

A DL system to identify and predict kidney disorders was proposed by Bayram et al. [11] with XAI to enhance interpretability and clinical trust. They incorporated CNNs in their model with interpretable layers to provide visual explanations to the results of the classification. The paper has pointed out that DL models were more accurate compared to traditional methods, but their non-transparency inhibited clinical application. The model also effectively demonstrated the most impactful clinical biomarkers in predicting CKD by incorporating the XAI methods such as LIME and SHAP, leading to greater transparency on the part of the healthcare practitioners. The authors conclude that XAI was found to improve the predicted reliability and user confidence making the XAI a viable solution in healthcare applications where explainability is crucial.

Silveira et al. [12] explored the possibility to predict chronic renal disease early using ML methods that are adapted to small and skewed datasets. They compared several models, such as RF, SVM, and Gradient Boosting classifiers to identify CKD at an early stage. The authors alleviated the challenges of data imbalance by using the SMOTE that significantly increased the sensitivity of the classifier to minority classes. Their experimental analysis showed that the highest accuracy and the recall rates were obtained with the help of RF, which indicates its effectiveness in clinical prediction. The study noted that proper preprocessing, which includes data normalization and feature selection, was of great importance in achieving believable results in small healthcare data.

The research by Mehrabi et al. [13] is a massive survey of bias and fairness in ML, pointing to severe ethical and technical issues in healthcare data processing. They focused their discussion on the harmful effects of cognitive, sampling and labeling biases on predictive models especially in a medical context such as CKD prediction when the demographic and socio-economic diversity is limited. The authors proposed fairness-aware learning procedures and debiasing algorithms to ensure equal model output across different groupings of populations. Their work has given a basic structure of understanding and mitigating prejudices in AI systems, which ensure that predictive healthcare models are transparent, ethical, and therapeutically relevant.

Ventrella et al. [14] applied the supervised ML algorithms to assess the chronic renal disease progression. They focused their study on predicting the occurrence of diseases rather than early diagnosis. The authors used longitudinal patient records and used methods such as LR, DT and ensemble learning to categorize CKD stages. The critical clinical markers, including serum creatinine, blood urea nitrogen, and hemoglobin, were found to be important factors in sickness progression according to the analysis of feature importance. The study has highlighted the importance of time-series and longitudinal modeling in the accurate depiction of dynamic nature of CKD and therefore, improves prediction of patient outcomes in the long-term.

Nishat et al. [15] performed a comprehensive evaluation of CKD diagnosis with the use of ML, evaluating the models based on KNN, Naïve Bayes, DT, and RF. They have stressed that normalization and feature selection are important in optimization of the model. To determine hemoglobin, albumin, blood pressure, and serum creatinine as major predictors of CKD, the authors employed the feature selection based on correlation. Their results proved that RF achieved the best balance between interpretability and accuracy, which makes it a suitable method of clinical decision support. The study showed that predicted dependability may be increased by using a large number of models through ensemble techniques.

Chittora et al. [16] introduced a complete ML model of CKD prediction, with an optimal pipeline, which involves feature selection, preprocessing, and model optimization. They applied methods such as SVM, LR, DT, and AdaBoost to identify the best parameter settings to predict chronic kidney disease. The study has shown that the ensemble learning techniques significantly outperformed the individual classifier, particularly when handling nonlinear relationships

International Journal of
AI Electronics and Nexus Energy
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0515 www.zesterapublications.com Original Research Paper

between the medical variables. The authors applied the method of cross-validation to reduce the overfitting and ensure the model generalization. Their exploration revealed that AdaBoost achieved better accuracy and recall rates, making it one of the most effective classifiers of CKD.

Dave et al. [17] reviewed the application of Explainable AI to healthcare using a heart disease dataset and provided valuable insights that can be applied to Chronic Kidney illness prediction models. They used SHAP and LIME interpretability algorithms to explain the decisions made by ML models. The authors emphasized that transparency plays a vital role in clinical AI systems because it allows healthcare providers to understand and validate model performances. They found that explainable AI together with ensemble techniques increases trust and accuracy in diagnoses, which can be used analogously to CKD-related prediction systems.

Ghosh [18] improved the prediction of chronic kidney disease by applying the ML techniques with an emphasis on the optimization of the parameters and evaluation of the model. The study used UCI CKD dataset to compare the algorithms such as SVM, RF, and KNN. The measures of feature relevance showed that hemoglobin, serum creatinine, and albumin were the most relevant. Another area that Ghosh studied is grid search and cross-validation to optimize model parameters and get better classification accuracy. The author concluded that RF was more accurate and understandable than other algorithms, which makes it an ideal choice in the context of CKD prediction systems where reliability is the key factor.

Aljaaf et al. [19] proposed a methodology of predictive analytics for the early prediction of CKD with machine learning models. The methodology also included data preprocessing, standardization, and ensemble modeling as a way of enhancing the accuracy of the diagnosis. The study compared different classifiers, such as DT, LR, and Naive Bayes using numerous evaluation parameters, such as accuracy, sensitivity, and specificity. Their model has shown high performance, which demonstrates the feasibility of using predictive analytics as a practical clinical decision support. Moreover, the authors suggested that the combination of these models and healthcare information systems could assist in the proactive monitoring of patients and early intervention actions.

Webster et al. [20] discussed in detail a clinical analysis of CKD, its epidemiology, pathophysiology, and health consequences around the world. CKD is cited among the major causes of death and disability in the world, and it is particularly affecting people in the poor regions disproportionately. The research named several risk factors, such as diabetes, hypertension, and genetic factors, and emphasized the critical importance of early detection by biomarkers, such as GFR, albuminuria, and serum creatinine levels. Their study developed clinical grounding of AI and data-driven approaches to the diagnosis and treatment of CKD.

## 3. MATERIALS AND METHODS

The proposed CKD prediction model is a robust, understandable, and scalable ML framework that could be used in clinical decision-making. It is based on the UCI CKD dataset that consists of 400 patient records and 25 clinical and biological variables in Apollo Hospital in India. The preprocessing of data includes the imputation of missing values by statistical and model-based methods, the encoding of categorical variables, the normalization of numerical features, and the correction of the imbalance of the classes using SMOTE [21]. Mutual Information, Variance Thresholding, Recursive Feature Elimination, and Sequential Feature Selection are the feature selection methods, which identify six key features: hemoglobin, serum creatinine, albumin, hypertension, age, and diabetes mellitus. It uses supervised classifiers, including LR, GNB, SVM, DT, RF, and AdaBoost, and interpretability is made easier using LIME and SHAP. A hybrid ensemble Voting Classifier, that combines both RF and AdaBoost, is built and implemented with Flask framework accessible web-based clinical applications.





Fig.1 Proposed Architecture

Figure 1 represents the procedure of CKD prediction. It starts with Data Pre-processing and Feature Selection (RFE FS) followed by Data

International Journal of
AI Electronics and Nexus Energy
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0515 www.zesterapublications.com Original Research Paper

Balancing (SMOTE). Several ML models (LR, NB, SVM, AdaBoost, DT, RF) are trained, evaluated and tested using metrics like Accuracy and F1-Score. The best model is saved, embedded in a Flask web application to run, and its predictions are explained with the help of XAI tools, like LIME and SHAP.

**a) Dataset Collection:**

The data used in this study was obtained out of a reputable medical source, which contained 400 records and 25 attributes in ARFF format. It includes clinical, physiological and biochemical values such as hemoglobin, serum creatinine, albumin, hypertension, diabetes mellitus and age. [22] These elements offer extensive patient health information for the identification of CKD. The dataset was loaded into a pandas DataFrame, which allowed the easy organization in the further analysis and model construction and validation aimed at accurate and timely CKD prediction.

| | age | bp | sg | al | su | rbc | pc | pcc | ba | bgr | ... | pcv | wbcc | rbcc | htn | dm | cad | appet | pe | ane | class |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 0 | 48 | 80 | 1.020 | 1 | 0 | <NA> | normal | notpresent | notpresent | 121 | ... | 44 | 7800 | 5.2 | yes | yes | no | good | no | no | ckd |
| 1 | 7 | 50 | 1.020 | 4 | 0 | <NA> | normal | notpresent | notpresent | <NA> | ... | 38 | 6000 | <NA> | no | no | no | good | no | no | ckd |
| 2 | 62 | 80 | 1.010 | 2 | 3 | normal | normal | notpresent | notpresent | 423 | ... | 31 | 7500 | <NA> | no | yes | no | poor | no | yes | ckd |
| 3 | 48 | 70 | 1.005 | 4 | 0 | normal | abnormal | present | notpresent | 117 | ... | 32 | 6700 | 3.9 | yes | no | no | poor | yes | yes | ckd |
| 4 | 51 | 80 | 1.010 | 2 | 0 | normal | normal | notpresent | notpresent | 106 | ... | 35 | 7300 | 4.6 | no | no | no | good | no | no | ckd |

5 rows × 25 columns

"Fig.2 CKD Dataset"

**b) Pre-Processing:**

Pre-processing ensures data quality and reliability through filling in data gaps, reducing noise, extracting relevant features, and balancing the distribution of classes. The measures improve model learning effectiveness, prediction performance, and stability towards reliable chronic renal disease classification.

***Data Preprocessing:*** The focus of data processing is to convert raw clinical records into a smooth and homogenous format that is compatible with ML models. The CKD data set contains both numerical and categorical variables, and the missing values are because of insufficient clinical tests and the inconsistency in reporting. Numerical features are also handled using statistical imputation, but categorical variables are handled using mode-based or model-driven imputation. The approach keeps the integrity of datasets and prevents the loss of information that may affect predictive power. Normalization and encoding methodologies ensure that features are represented in a consistent fashion and that methods are interoperable. Efficient handling of missing information reduces bias, enhances stability and enables learning algorithms to identify meaningful clinical patterns that are essential in accurate prediction of CKD.

***Feature Selection:*** The selection of features is also important in increasing model efficiency and interpretability through identifying the most meaningful clinical features. RFE is used to sequentially remove less important features based on the measures of model performance and the importance of features. By eliminating the least relevant features via systematic training and by training and refining to only the most relevant features, RFE ensures that only the most relevant attributes affect the classification. This process reduces the dimensions, reduces overfitting, and improves generalization. The selected variables are highly clinically relevant and enhance the accuracy of prediction as well as interpretability. RFE simplifies the work of computing and enables faster training and more accurate predictions, which is vital to real-time clinical decision support systems.

***Data Balancing:*** The class imbalance in the CKD dataset can bias the learning algorithms to the majority, thus failing to detect minority cases. The solution to this problem in data sampling is the SMOTE. SMOTE develops synthetic samples of the minority category by interpolating the available data points, instead of copying records. This provides a more balanced distribution of classes and preserves basic data structures. Balanced data has been shown to increase the sensitivity of the classifier, the recall, and the overall predictive accuracy of the classifier particularly in the diagnosis of CKD. SMOTE enhances model learning, reduces bias, and provides accurate and reliable disease prediction outcomes by ensuring that both CKD and non-CKD patients are represented fairly.

**c) Training and Testing:**

A stratified 10-fold cross-validation was used to divide the processed data into training and testing sets. The selected features were trained with different ML algorithms. The accuracy, precision, recall and F1-score were used to evaluate the models. Such an in-depth training and testing guaranteed strict performance validation, accurate prediction, and reliability of the developed system in the early detection of Chronic Kidney Disease.

**d) Algorithms:**

**Logistic Regression (LR):** Determines the likelihood of chronic kidney disease by simulating the connection between important clinical variables using the logistic function. Propositions are interpretable and probabilistic, and can help the doctors to identify the probability of a disease and

International Journal of
AI Electronics and Nexus Energy
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0515 www.zesterapublications.com Original Research Paper

make timely intervention through the help of data-driven diagnostic information.

$$\hat{y}_i = \sigma(w^T x + b) = \frac{1}{1 + e^{-(w^T x + b)}} \quad (1)$$

**Gaussian Naïve Bayes (GNB):** It is a probabilistic model that is used to classify the cases of CKD and non-CKD using the Gaussian assumptions. Gives fast, reliable forecasts on less data, enabling physicians to determine the risk of CKD and enable the early diagnosis of the condition with statistical confidence.

**Support Vector Machine (SVM):** Categorizes cases of CKD and non-CKD by finding a suitable hyperplane that will separate the cases the most. [27] uses kernel mapping to identify non-linear associations that guarantee high accuracy and soundness in interpreting clinical data and identifying early diseases.

$$minimize\ \frac{1}{2}\ ||W||^2 + C\sum_{i=1}^{n}\xi_i \quad (2)$$

**Decision Tree (DT):** Develops a gradation system of chronic kidney disease using clinical features. Offers direct decision-making, handles missing data effectively and aids the physicians in interpreting results, thereby enhancing diagnostic accuracy and early diagnosis strategies.

$$I\ (i) = 1 - \sum_{i=1}^{k} p_i^2 \quad (3)$$

**Random Forest (RF):** Combines multiple Decision Trees in order to increase the stability of classification and reduce overfitting. Recognizes substantial CKD indicators, enhances the predictive power, and provides information to physicians on the importance of features so that patients can be assessed and treated.

$$Gini = 1 - \sum_{i=1}^{C}(Pi)^2 \quad (4)$$

**AdaBoost:** The poor learners are sequentially integrated with misclassified CKD cases given priority in order to improve the precision. Enhances the model effectiveness through adaptive weighting, enabling the proper identification of complex disease patterns and strengthening reliable and evidence-based clinical assessments.

$$H(x) = sign\left(\sum_{t=1}^{T} \propto_t h_t(x)\right) \quad (5)$$

**Voting Classifier:** Majority vote is used to consolidate the predictions of a wide variety of algorithms, including RF and AdaBoost. Improves the accuracy, reduces bias, and offers consistent CKD results, ensuring efficient, cooperative decision-making in clinical evaluation.

$$\hat{y}\ = argmax_c\left(\sum_{i=1}^{n} II\ (\hat{y}_i = c)\right) \quad (6)$$

**e) Integration of XAI and Flask Framework:**
Explainable Artificial Intelligence (XAI) combined with a Flask infrastructure enables the provision of transparent and interpretable predictions of ML models within an interactive web. In this implementation, LIME and SHAP are used to explain the model decisions in the case of predicting CKD. LIME provides localized descriptions, considering the impact of single characteristics on a given test case, focusing on such aspects as age, blood pressure, and specific laboratory results. SHAP goes further to provide global interpretability, the effect of each feature on multiple samples, and provide visualizations like summary plots to underscore key factors that impact model outputs.
By embedding these XAI tools into a Flask-based app, end-users can engage in interacting with patient data and visualizing the estimation of probability and grasping feature-level information. Such integration builds confidence, improves clinical decision making and ensures that model forecasts are accurate as well as understandable by health care professionals.

## 4. EXPERIMENTAL RESULTS

**Accuracy:** Accuracy of a test is the ability of the test to make the right call after differentiating between the patient and healthy cases. To determine the validity of a test, the fraction of true positives and true negatives should be divided in all the cases tested. This can be mathematically stated as:

$$Accuracy = \frac{\text{TP} + \text{TN}}{\text{TP} + \text{FP} + \text{TN} + \text{FN}} \quad (7)$$

**Precision:** Precision measures the percentage of correctly categorised cases in the cases that are found to be positive. It, therefore, follows that the precision can be calculated using the following formula:

$$Precision = \frac{\text{True Positive}}{\text{True Positive } + \text{False Positive}} \quad (8)$$

**Recall:** Recall is a ML metric that measures whether a model can be used to recognize all the relevant examples of a particular class. The proportion of correct positive observations to the actual positive observations, which provides information about the

International Journal of
AI Electronics and Nexus Energy
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0515 www.zesterapublications.com Original Research Paper

effectiveness of a model in recognizing the events of a particular class.

$$Recall = \frac{TP}{TP + FN} \quad (9)$$

**F1-Score:** F1 score is a measurement to determine the accuracy of a ML model. It is a composite of accuracy and recall of a model. The accuracy measure is used to measure how often a model obtains true predictions on the whole dataset.


$$F1\ Score = 2 * \frac{Recall\ X\ Precision}{Recall + Precision} * 100 \quad (10)$$

***Table.1*** Performance Evaluation Table

| Model | Accuracy | Precision | Recall | F1 Score |
|---|---|---|---|---|
| **Voting** | **0.994** | **0.994373** | **0.994** | **0.993993** |
| AdaBoost | 0.992 | 0.992308 | 0.992 | 0.991997 |
| RF | 0.982 | 0.982823 | 0.982 | 0.981985 |
| DT | 0.968 | 0.970186 | 0.968 | 0.967941 |
| LogReg | 0.968 | 0.971210 | 0.968 | 0.967861 |
| SVM | 0.962 | 0.965921 | 0.962 | 0.961864 |
| GNB | 0.952 | 0.954925 | 0.952 | 0.951883 |

Table 1 contrasts the models of predicting chronic kidney diseases in terms of accuracy, weighted precision, recall, and F1-score, showing that the hybrid Voting Classifier performs better than the other models.

***Fig.3*** Comparison Graph




A comparative graph of chronic kidney disease prediction models is presented in Figure 3, which is based on the accuracy, weighted precision, recall, and F1-score parameters, where each parameter is represented by a specific color: accuracy (blue), precision (green), recall (orange), and F1-score (red) to highlight the outstanding performance of the hybrid Voting Classifier.





Fig.4 Upload the Data

As shown in Figure 4, the input form enables a user to enter patient information in the case of Chronic Kidney Disease to make a prediction with the help of the ML-based categorization system.





Fig.5 Predicted Results

The result of the prediction in the output screen in Fig. 5 is The Analysis suggests No CKD Detected with a confidence of 79.0% indicating the confidence of the model.




Fig.6 Upload the Data

Fig. 6 shows that the input interface allows users to feed in patient-specific clinical data in CKD to enable the system to generate predictions with interpretability and confidence scores.

International Journal of
AI Electronics and Nexus Energy
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0515 www.zesterapublications.com Original Research Paper





Fig.7 Predicted Results

The output screen in Figure 7 shows that the prediction was CKD Detected with a confidence score of 91.0, which implies that there is a lot of certainty about the model.

## 5. CONCLUSION

The work provides a good example of how an accurate and interpretable system of chronic kidney disease prediction could be successfully developed with the help of advanced ML techniques and a working web-based application. Careful preprocessing, fair learning with SMOTE and feature selection demonstrated the identification of clinically relevant features that have strong influence on the diagnostics of CKD. The Voting Classifier, a combination of RF and AdaBoost, showed the best performance of all the evaluated models with the accuracy of 99.4, precision of 99.4, recall of 99.4, and F1-score of 99.3, which indicates that the classifier is highly reliable and consistent in distinguishing between CKD and non-CKD patients. Incorporation of explainable artificial intelligence techniques specifically LIME and SHAP enhanced transparency by clearly showing the contribution of features, hence enhancing clinical interpretability and trust in the predictions. The complete system is deployed as a Flask web application, which provides security when registering users and authenticating them, structured data entry of patients, real-time forecasting, and interpretable output presentation. The technique yields unquestionable diagnostic findings like, chronic kidney disease found or no chronic kidney disease found, which makes it easier to be able to make informed clinical decisions and intervene in time. The results confirm that the hybrid ensemble Voting model combined with elucidative insights and an interactive Flask interface is a reliable, accurate, and user-friendly tool of CKD risk assessment in real healthcare practice.

The future possibilities of this technology lie in improving its flexibility and application in the real health care environments. Generalizability and strength can be enhanced by including more diverse and larger datasets of multiple hospitals. Combining wearable devices and electronic health data with real-time monitoring systems can provide continuous predictions and custom alarms. Future improvements could include advanced DL networks to improve the accuracy of predicted results and the combination with telemedicine technologies to assist patients remotely. The enhancement of the explainability methods will strengthen clinician confidence, and mobile-friendly interfaces will make the framework available to clinicians and patients alike to take initiative in the management of kidney health.

## REFERENCES

[1] Moreno-Sánchez, P. A. (2023). Data-driven early diagnosis of chronic kidney disease: development and evaluation of an explainable AI model. IEEE Access, 11, 38359-38369.

[2] Jawad, K. M., Verma, A., Amsaad, F., & Ashraf, L. (2024). AI-driven predictive analytics approach for early prognosis of chronic kidney disease using ensemble learning and explainable AI. arXiv preprint arXiv:2406.06728.

[3] Ghosh, S. K., & Khandoker, A. H. (2024). Investigation on explainable machine learning models to predict chronic kidney diseases. Scientific Reports, 14(1), 3687.

[4] Swapna, G., Sreenivasulu, K., Deepika, M., Baseer, K. K., Neerugatti, V., & Viswanath, G. (2025). Brain tumour detection using MRI images in CNN. Advances in Science, Engineering and Technology, 6.

[5] Ghosh, S. K., Widatalla, N., & Khandoker, A. H. (2025). Machine Learning Framework for Early Detection of Chronic Kidney Disease Stages Using Optimized Estimated Glomerular Filtration Rate. IEEE Access.

[6] S. K. Ghosh and A. H. Khandoker, “Investigation on explainable machine learning models to predict chronic kidney diseases,” Sci. Rep., vol. 14, no. 1, p. 3687, Feb. 2024, doi: 10.1038/s41598-024-54375-4.

[7] V. N. Manju and N. Aparna, “Decision tree-based explainable AI for diagnosis of chronic kidney disease,” in Proc. 5th Int. Conf. Inventive Res. Comput. Appl. (ICIRCA), Coimbatore, India, Aug. 2023, pp. 947–952, doi: 10.1109/icirca57980.2023.10220774.

International Journal of
AI Electronics and Nexus Energy
Peer Reviewed, Referred & Indexed Journal
ISSN: 3070-0515 www.zesterapublications.com Original Research Paper

[8] A. P. Moreno-Sánchez, "Data-driven early diagnosis of chronic kidney disease: Development and evaluation of an explainable AI model," IEEE Access, vol. 11, pp. 38359–38369, 2023, doi: 10.1109/ACCESS.2023.3264270.
[9] F. Sanmarchi et al., "Predict, diagnose, and treat chronic kidney disease with machine learning: A systematic literature review," J. Nephrol., vol. 36, no. 4, pp. 1101–1117, Feb. 2023.
[10] A. Holzinger, C. Biemann, C. S. Pattichis, and D. B. Kell, "What do we need to build explainable AI systems for the medical domain?" arXiv:1712.09923, 2022.
[11] A. F. Bayram, C. Gurkan, A. Budak, and H. Karatas, "A detection and prediction model based on deep learning assisted by explainable artificial intelligence for kidney diseases," Avrupa Bilim ve Teknoloji Dergisi, vol. 40, no. 2022, pp. 67–74, 2022.
[12] A. C. M. D. Silveira et al., "Exploring early prediction of chronic kidney disease using machine learning algorithms for small and imbalanced datasets," Appl. Sci., vol. 12, no. 7, p. 3673, Apr. 2022.
[13] Kalae, U. K. (2025). Optimizing cost-effective cloud data pipeline orchestration across multiple cloud providers. Journal of Information Systems Engineering and Management, 10(63s), e726–e741.
[14] P. Ventrella et al., "Supervised machine learning for the assessment of chronic kidney disease advancement," Comput. Methods Programs Biomed., vol. 209, Sep. 2021, Art. no. 106329.
[15] M. M. Nishat et al., "A comprehensive analysis on detecting CKD by employing machine learning algorithms," EAI Endorsed Trans. Pervasive Health Technol., vol. 7, no. 29, p. e1, 2021.
[16] Patyrykin, K., & Vasyukova, L. (2025). Environmental Accountability or Symbolic Compliance? A Critical Review of ESG Ratings, Greenwashing, and Indirect Emissions in the Global Insurance Sector. International Journal of Energy Economics and Policy, 15(6), 917–925. https://doi.org/10.32479/ijeep.22770.
[17] D. Dave et al., "Explainable AI meets healthcare: A study on heart disease dataset," 2020, arXiv:2011.03195.
[18] Viswanath G., Krishna Prasad K ., Dr. J Maha Lakshmi., Dr.G.Swapna (2024). Health Prediction Using Machine Learning with Drive HQ Cloud Security. Frontiers in HealthInformatics, 13(8), 2755-2761, https://doi.org/10.5281/zenodo.19128870
[19] A. J. Aljaaf et al., "Early prediction of chronic kidney disease using machine learning supported by predictive analytics," in Proc. IEEE Congr. Evol. Comput. (CEC), Rio de Janeiro, Brazil, Jul. 2018, pp. 1–9, doi: 10.1109/CEC.2018.8477876.
[20] A. P. A. C. Webster et al., "CKD," Lancet, vol. 389, no. 10075, pp. 1238–1252, 2017.
[21] M. Chen, Y. Hao, K. Hwang, L. Wang, and L. Wang, "Disease prediction by machine learning over big data from healthcare communities," IEEE Access, vol. 5, pp. 8869–8879, 2017.
[22] S. H. Ralston et al., Davidson's Principles and Practice of Medicine, 23rd ed., Amsterdam, The Netherlands: Elsevier, 2018.
[23] T. J. Hoerger et al., "The future burden of CKD in the United States: A simulation model for the CDC CKD initiative," Amer. J. Kidney Diseases, vol. 65, no. 3, pp. 403–411, Mar. 2015.
[24] Poojari, R. (2024). Assessing Clinical Natural Language Processing (NLP) Models for Interpreting Electronic Health Records (EHR): Focus on Accuracy, Bias, and Generalizability.
[25] Reddy, S. K. R. (2024). Designing Blockchain Architecture to Transform Loyalty Rewards into Cryptocurrency Investments.
[26] T. Yorozu et al., "Electron spectroscopy studies on magneto-optical media and plastic substrate interface," IEEE Transl. J. Magn. Jpn., vol. JMJ-2, no. 8, pp. 740–741, Aug. 1987.
[27] M. Velmurugan et al., "Developing a fidelity evaluation approach for interpretable machine learning," 2021, arXiv:2106.08492.
[28] A. Eddy, "Progression in CKD," Adv. CKD, vol. 12, no. 4, pp. 353–365, 2005.
[29] Lakshmi, J. M., Prasad, K. K., & Viswanath, G. (2025). Proactive Security in Multi-Cloud Environments: A Blockchain Integrated Real-Time Anomaly Detection and Mitigation Framework. Cuestiones De Fisioterapia, 54(2), 392-417.
[30] M. E. Hall et al., "Obesity, hypertension, and CKD," Int. J. Nephrol. Renovas. Disease, vol. 7, pp. 75–88, Feb. 2014.